



导向轴支座



支架型

紧凑 / 带键槽型

■ 紧凑标准型




■ 紧凑长导向型



代码		材质	表面处理	附件
标准型	长导向型			
ABSMFB	ABSMFBL	S45C	发黑	1个内六角螺栓
ABSMF	ABSMFL		无电解镀锌	1个内六角螺栓 (SUS)
ABSSMF	ABSSMFL	SUS304	—	


■ 紧凑标准型

ABSMFB
ABSMF
ABSSMF



■ 紧凑长导向型

ABSMFBL
ABSMFL
ABSSMFL



6.3/(1.6/)



1 代码 2 D
ABSMFB16

■ 请按步骤①~②选择型号和参数后进行订购。



型号区分: 7 天发货

型号		L	L ₁	H	B	T	T ₁	P	d ₁	d ₂	S	X	Y	M	d	R			
① 代码	② DH7																		
标准型	8	16	—	30	11	3.5	—	20	4.5	8	1.5	9.5	5	5	5.5	9			
ABSMFB	10		—	34		4.5	—	22	5.5	9.5		10	6		6.6	12			
ABSMF	12	17	25	36			12.5	25				12							
ABSSMF	15		28	38			15.5	26				13							
长导向型	16		30	39	14	6	14	28	6.6	11	2	13.5	7	6	6.6	12			
ABSMFBL	20	22	34	49			18	35				16	8						
ABSMFL	25		38	54			22	40				19							
ABSSMFL (D12 ~ 30)	30	24	40	59			24	45				22							


■ 外径比较表

D (内径)	外径 (H)		
	紧凑型	开口·标准型	差
8	30	39	-9
10	34	49	-15
12	36	52	-16
15	38	56	-18
16	39	56	-17
20	49	64	-15
25	54	69	-15
30	59	79	-20

■ 带键槽型



圆法兰型	两面切割法兰型	材质	表面处理
ABSFBN	ABSHBNG	S45C	发黑
ABSFNG	ABSHNG		无电解镀锌



■ 圆法兰型
ABSFBN
ABSFNG

■ 两面切割法兰型
ABSHBNG
ABSHNG

6.3/(1.6/)

型号		固定部壁厚 (N)	L	D1	H	T	ℓ	M (粗牙螺纹)	P	W	P1	F	d1	b	公差	t	公差
① 代码	② DH7																
圆法兰型 两面切割法兰型 ABSFBN ABSHBNG ABSFNG ABSHNG	12	+0.018	5	24	22	40	6	15	32	25	28	16	4.5	4	±0.015	1.8	+0.1
	16	0	6	32	28	50	19	M4	40	32	33	22	5.5	5		2.3	0
	20			32	35	63	20	M5	50	40	42	25	6.6	6		2.8	+0.2
	25	+0.021	7.5	40	40	68	23		55	45	45	30					
	30	0		38	45	73	10	M6	60	50	48	35		8	±0.018	3.3	0

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613