





代码		材质	表面处理	附件 止动螺丝
标准型	嵌入型			
BBHSB	BBHTB	S45C	发黑	SCM435 2个
BBHS	BBHT	S45C	无电解镀镍	SUS304 2个
BBSHS	—	SUS304	—	

$$\frac{6.3}{\nabla} \left(\frac{1.6}{\nabla} \right)$$


标准型




嵌入型



d7~14



d17~30



型号(① 代码 · ② d)
BBHSB20

■ 请按步骤①~②选择型号和参数后进行订购。



型号区分：
代码 **7** 天发货

型号				可订购型号																		
① 代码	②d	DH7	公差	B	H	W	T	dz	D ₁	D ₂	D _{3g7}	公差	T ₁	B ₁	A	F	M (d ₂)	d ₁	H ₁	使用的轴承	BBHSB BBHTS BBHT	BBSHS
(标准型) BBHSB BBHS BBSHS	(嵌入型) 7	19	+0.021 0	23	54	38	22	10	25	27	24	-0.007 -0.028	14	15.5	41	—	M8 (6.8)	11	6.5	BAKXZ 7	●	●
	9	21			56	40		12	27	29	26				43					BAKXZ 9	●	●
	12	24			60	15		29	31	30	46				BAKXZ12					●	●	
	14	26		25	66	44	24	17	31	33	34	16	17	52	50	BAKXZ14	●	●				
(标准型) BBHSB BBHTS BBHT	(嵌入型) 17	30	+0.025 0	30	77	54	29	20	36	38	36	-0.009 -0.034	20	20.5	50	32	M10 (8.5)	14	8.6	BAKXZ17	●	—
	20	37			88	58		25	43	45	45				59	36				BAKXZ20	●	—
	25	42			94	64		30	48	50	50				64	39				BAKXZ25	●	—
	30	47		96	66	35	53	55	54	-0.010 -0.040	18	21	66	40	BAKXZ30	●	—					

轴承座组件

13

邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达