



定位销/夹具衬套

夹具衬套 直柱·薄壁型



型号(①代码·②d) — ③L
DAAU8 — 8

■ 请按步骤①~③选择型号和参数后进行订购。



型号区分: ④代码 7天发货

定位销
夹具衬套

20

薄壁型

代码		材质	表面处理	硬度
D尺寸p6	D尺寸m6			
DAAUP	DAAU	SUJ2 或 SKS3	—	淬火硬度58HRC~
DAAUNP	DAAUN			
DAAUCP	DAAUC	SUS440C	—	淬火硬度50~55HRC

d	d公差	
	无表面处理	无电解镀锌
3	+0.008 +0.002	+0.010 0
4	+0.012 +0.004	+0.012 0
5		
6		
8	+0.014 +0.005	+0.014 +0.005
10		
12	+0.017 +0.006	+0.017 +0.006
13		
15		
16		
20	+0.020 +0.007	+0.020 +0.007
25		

D	D公差	
	p6	m6
5	+0.020	+0.012
6	+0.012	+0.004
7	+0.024 +0.015	+0.015 +0.006
8		
10	+0.029 +0.018	+0.018 +0.007
13		
15		
17	+0.035 +0.022	+0.021 +0.008
19		
21	+0.042 +0.026	+0.025 +0.009
26		
31		

型号		③L选择						D	壁厚(N)	R			
①代码	②d	3	4	5	6	8	10						
<p6> DAAUP DAAUNP DAAUCP	<m6> DAAU DAAUN DAAUC	3	6	8	10	12		5	1	0.5			
		4	6	8	10	12	15	16	6	1	0.5		
		5	6	8	10	12	15	16	20	7	1	0.5	
		6	6	8	10	12	15	16	20	8	1	0.5	
		8	6	8	10	12	15	16	20	10	1	0.5	
		10	6	8	10	12	15	16	20	13	1.5	0.5	
		12		8	10	12	15	16	20	15	1.5	0.5	
		13			10	12	15	16	20	17	2	1	
		15				12	15	16	20	19	2	1	
		16				12	15	16	20	21	2.5	2	
		20				12	15	16	20	25	26	3	2
		25							20	25	31	3	2

