



型号(①代码·②No.)

FBNA10

■请按步骤①~②选择型号和参数后进行订购。



型号区分:

代码

7天发货

代码	材质	硬度(JIS HS)	颜色	可使用温度范围	JIS符号	用途	特长
FBNA	丁腈橡胶	70±5	黑色	-30~100℃	1种A	耐矿物油用	是最有代表性的材料。具有优良的耐油性、耐磨性以及稳定的耐热性的标准材料。
FBNBR	氟树脂	-	白色	依据O形圈	-	高压用	仅用O形圈耐压性能不足时辅助用的保护垫圈。

FBNA

FBNBR

■ JIS B 2401 P系列 (固定用·运动用)

型号 代码	No.	JIS 公称编号	W	内径		配套材料							
				do	公差	d	公差	D	公差				
FBNA	3	P3	1.9 ±0.08	2.8	±0.14	3	0	6	+0.05 0				
	4	P4		3.8		4		7					
	5	P5		4.8		5		8					
	6	P6		5.8	±0.15	6		-0.05		9	+0.05 0		
	7	P7		6.8		7				10			
	8	P8		7.8	±0.16	8				0		11	+0.06 0
	9	P9		8.8		9						12	
	10	P10	9.8	±0.17	10	-0.06	13		+0.08 0				
	10A	P10A	9.8		10		14						
	11	P11	10.8	±0.18	11		0					15	
	11.2	P11.2	11		11.2			15.2					
	12	P12	11.8	±0.19	12			-0.06			16	+0.08 0	
	12.5	P12.5	12.3		12.5					16.5			
	14	P14	13.8	±0.20	14					0	18		+0.06 0
	15	P15	14.8		15	19							
	16	P16	15.8	±0.21	16	-0.08			20		+0.08 0		
	18	P18	17.8		18		22						
	20	P20	19.8	±0.22	20		0		24				
	21	P21	20.8		21			25					
	22	P22	21.8	±0.23	22			-0.08	26			+0.08 0	
	22A	P22A	21.7		22				28				
	22.4	P22.4	22.1	±0.24	22.4				0	28.4			+0.08 0
	24	P24	23.7		24	30							
	25	P25	24.7	±0.25	25	-0.08				31	+0.08 0		
	25.5	P25.5	25.2		25.5		31.5						
	26	P26	25.7	±0.26	26		0			32			
	28	P28	27.7		28			34					
	29	P29	28.7	±0.28	29			-0.08		35		+0.08 0	
	29.5	P29.5	29.2		29.5				35.5				
	30	P30	29.7	±0.29	30				0	36			+0.08 0
	31	P31	30.7		31	37							
	31.5	P31.5	31.2	±0.30	31.5	-0.08				37.5	+0.08 0		
	32	P32	31.7		32		38						
	34	P34	33.7	±0.31	34		0			40			
	35	P35	34.7		35			41					

型号 代码	No.	JIS 公称编号	W	内径		配套材料							
				do	公差	d	公差	D	公差				
FBNA	35.5	P35.5	3.5 ±0.1	35.2	±0.34	35.5	0	41.5	+0.08 0				
	36	P36		35.7		36		42					
	38	P38		37.7	38	44							
	39	P39		38.7	±0.37	39		-0.08		45	+0.08 0		
	40	P40		39.7		40				46			
	41	P41		40.7	±0.38	41				0		47	+0.08 0
	42	P42		41.7	±0.39	42						48	
	44	P44		43.7	±0.41	44				0		50	+0.1 0
	45	P45		44.7		45						51	
	46	P46		45.7	±0.42	46						52	
	48	P48	47.7	±0.44	48	54							
	50	P50	49.7	±0.45	50	56							
	50A	P50A	49.7	±0.45	50	-0.1	60		+0.1 0				
	52	P52	51.6		±0.47		52	62					
	53	P53	52.6	±0.48	53		63						
	55	P55	54.6	±0.49	55		65						
	56	P56	55.6	±0.50	56		66						
	58	P58	57.6	±0.52	58		68						
	60	P60	59.6	±0.53	60		70						
	62	P62	61.6	±0.55	62		72						
63	P63	62.6	±0.56	63	73								
65	P65	64.6	±0.57	65	75								
67	P67	66.6	±0.59	67	77								
70	P70	69.6	±0.61	70	80								
71	P71	70.6	±0.62	71	81								
75	P75	74.6	±0.65	75	85								
80	P80	79.6	±0.69	80	90								



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达