



P尺寸固定·L尺寸选择型

型号(①代码·③P) — ④L
DAY6 — 12

■请按步骤①~④选择型号和参数后进行订购。



型号区分: 7天发货

P尺寸·L尺寸自由指定型

型号(①代码·②D) — ③P — ④L
DAYF10 — P6.00 — L5.0


■圆法兰型





代码				材质	表面处理	硬度
P尺寸固定·L尺寸选择型		P尺寸·L尺寸自由指定型				
4点固定	3点固定	4点固定	3点固定	SKS3	—	淬火硬度56~60HRC
DAY	DAT	DAYF	DATF			
—	—	DAYFB	—	SKS3	发黑	淬火硬度56~60HRC
DAYM	—	DAYFM	DATFM	SKS3	无电解镀镍	淬火硬度56~60HRC
—	—	DAYFC	—	SUS440C	—	淬火硬度50~55HRC
—	—	DAYFS	—	SUS304	—	—

$$6.3 / (\sqrt{1.6} / \sqrt{0.8} / \sqrt{G})$$

4点固定



3点固定



Dg6	D公差 g6
10	-0.005 -0.014
12	-0.006 -0.017
15	-0.007 -0.020
18	-0.009 -0.025
22	-0.007 -0.020
25	-0.007 -0.020
26	-0.007 -0.020
30	-0.009 -0.025
35	-0.009 -0.025

■P尺寸固定·L尺寸选择型—4点固定—

型号	①代码	③P	④L选择	R	H	T	Dg6	A	d	d1	h
DAY DAYM	5	8 10 12 *16	1	25	5	10	17	3.3	6.5	3.5	3.5
	6	8 10 12 16	1	25	5	10	17	3.3	6.5	3.5	3.5
	8	10 12 16 20	2	28	5	12	20	3.3	6.5	3.5	3.5
	10	10 12 16 20	2	36	6	15	26	4.5	8	4.5	4.5
	12	12 16 20 25 30	2	36	6	18	26	4.5	8	4.5	4.5
	13	12 16 *20 25 *30	2	40	6	22	30	4.5	8	4.5	4.5
	15	12 16 20 25 30	2	44	6	25	34	4.5	8	4.5	4.5
	16	16 20 25 30 35	2	44	6	26	34	4.5	8	4.5	4.5
	20	16 20 25 30 35	3	56	8	30	42	6.6	11	6.5	6.5
	25	20 25 30 *35 40	3	60	8	35	46	6.6	11	6.5	6.5

⊗DAYM不可选择带*的尺寸

■P尺寸固定·L尺寸选择型—3点固定—

型号	①代码	③P	④L选择	R	H	T	Dg6	A	d	d1	h
DAT	6	8 10 12 16	1	25	5	10	17	3.3	6.5	3.5	3.5
	8	10 12 16 20	2	28	5	12	20	3.3	6.5	3.5	3.5
	10	10 12 16 20	2	36	6	15	26	4.5	8	4.5	4.5
	12	12 16 20 25 30	2	36	6	18	26	4.5	8	4.5	4.5
	15	12 16 20 25 30	2	44	6	25	34	4.5	8	4.5	4.5
	20	16 20 25 30 35	3	56	8	30	42	6.6	11	6.5	6.5

■P尺寸·L尺寸自由指定型

型号	①代码	②Dg6	③P最小单位 0.01mm	④L最小单位 0.1mm	R	H	T	A	d	d1	h
4点固定 DAYF DAYFB DAYFM DAYFC DAYFS	10	4.00~6.50	5.0~15.0	10.0~35.0	1	25	5	17	3.3	6.5	3.5
	12	6.00~8.50			2	28	5	20	3.3	6.5	3.5
	15	8.00~10.50			2	36	6	26	4.5	8	4.5
	18	10.00~12.50			2	36	6	26	4.5	8	4.5
	20	12.00~13.50			2	40	6	30	4.5	8	4.5
	22	12.00~13.50			2	40	6	30	4.5	8	4.5
3点固定 DATF DATFM	25	13.00~15.50	12.0~50.0	2	44	6	34	4.5	8	4.5	
	26	15.00~16.50		2	44	6	34	4.5	8	4.5	
	30	16.00~20.50		3	56	8	42	6.6	11	6.5	
	35	20.00~25.00		3	60	8	46	6.6	11	6.5	

⊙L+T≤P×3.0



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达