



弹簧/缓冲器/氮气弹簧

扭簧



型号(1)代码·(2)内径

LBSA90R4

(3)圈数

3

(4)线径

0.5

■ 请按步骤①~④选择型号和参数后进行订购。



型号区分:

5 天发货

代码

■ 90°右旋型



■ 180°左旋型



臂角90°

LBSA90R(右旋转)

LBSA90L(左旋转)

臂角135°

LBSA135R(右旋转)

LBSA135L(左旋转)

臂角180°

LBSA180R(右旋转)

LBSA180L(左旋转)

③圈数 n

③圈数 n

③圈数 n

材质 SUS304-WPB

* 上图为右旋型。

① 请沿着螺旋方向使用扭簧。

型号		③圈数 n	④线径 d	臂长 L · R	弹簧常数(扭矩) N · mm/deg			使用最大角度 deg(度)		
①代码	②内径 D				臂角 90°	臂角 135°	臂角 180°	臂角 90°	臂角 135°	臂角 180°
臂角90° LBSA90R(右旋型) LBSA90L(左旋型)	2	2	0.2	20	0.0115	0.0119	0.0124	41	40	36
			0.3		0.0563	0.0586	0.0611	26	25	23
			0.2		0.0088	0.0090	0.0093	59	58	56
		3	0.3		0.0428	0.0441	0.0455	38	36	35
			0.3		0.0345	0.0354	0.0363	52	50	47
			0.4		0.1054	0.1080	0.1108	38	36	34
	3	4	0.3	30	0.0289	0.0295	0.0302	61	60	58
			0.4		0.0882	0.0900	0.0920	46	45	43
			0.3		0.0387	0.0403	0.0420	40	38	36
		5	0.4		0.1199	0.1248	0.1301	30	27	25
			0.3		0.0295	0.0304	0.0314	56	54	52
			0.4		0.0912	0.0940	0.0970	42	40	39
臂角135° LBSA135R(右旋型) LBSA135L(左旋型)	4	4	0.4	40	0.0736	0.0755	0.0774	55	53	51
			0.5		0.1756	0.1799	0.1845	44	42	41
			0.4		0.0617	0.0630	0.0643	71	68	66
		5	0.5		0.1471	0.1501	0.1533	54	53	51
			0.4		0.0918	0.0955	0.0996	39	37	34
			0.5		0.2206	0.2296	0.2394	29	28	27
臂角180° LBSA180R(右旋型) LBSA180L(左旋型)	5	4	0.4	50	0.0700	0.0722	0.0744	56	54	52
			0.5		0.1680	0.1732	0.1787	42	41	40
			0.6		0.1357	0.1390	0.1425	57	54	52
		5	0.6		0.2763	0.2831	0.2903	48	47	45
			0.5		0.1138	0.1161	0.1185	69	67	65
			0.6		0.2315	0.2363	0.2413	60	59	58
(弹簧常数为将臂长切割成L/2、R/2时的参考值。 1N=0.101972kgf 1deg=1°(角度))	6	5	0.5	60	0.1793	0.1866	0.1944	39	36	34
			0.6		0.3672	0.3821	0.3983	31	30	27
			0.5		0.1368	0.1409	0.1454	55	52	51
		6	0.6		0.2797	0.2883	0.2974	47	44	42
			0.6		0.2259	0.2314	0.2373	60	58	56
			0.8		0.6936	0.7108	0.7289	42	41	40
	6	5	0.6	60	0.1894	0.1933	0.1974	75	73	71
			0.8		0.5811	0.5931	0.6056	54	53	52
			0.8		0.3099	0.3224	0.3360	37	36	34
		6	0.8		0.9590	0.9981	1.0406	26	25	24
			0.6		0.2363	0.2436	0.2512	56	52	50
			0.8		0.7299	0.7523	0.7762	38	36	35
	6	5	0.8	60	0.5891	0.6037	0.6190	50	48	47
			1.0		1.4045	1.4394	1.4760	42	40	39
			0.8		0.4939	0.5041	0.5147	63	61	60
			1.0		1.1765	1.2008	1.2262	51	50	49



型号(1)代码·(2)D

LBSA90R4

(3)n

3

(4)d

0.5

— (LC · RC · LBC · RBC)

LBSA90R4 — 3 — 0.5 — LC12-RC15-LBC90-LZ5

可选加工 代码	追加臂长切割加工		弯曲左臂		弯曲右臂	
	LC	RC	LBC		RBC	
技术说明			(右旋型) 	(右旋型) 		
			(左旋型) 	(左旋型) 		
			将臂长切成LC、RC的长度。 ● LC≥3、RC≥3 最小单位 1mm [指定方法] LC12		● LBC…指定弯曲方向(请参阅上图) ① 从LBC0、LBC90、LBC180、LBC270中选择 ● LZ…指定弯曲位置(指定单位1mm) ① LZ≥3 L—LZ≥3 [指定方法] LBC90—LZ10	

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613