



型号 (1 代码 · 2 M) - (3 L)  
EBSC2 - 3

■ 请按步骤 ①~③ 选择型号和参数后进行订购。



型号区分: 5 天发货  
代码

代码	材质	强度分类
EBSC	SUS304	A2-70

① JIS B 1176

※强度分类是指螺栓的抗拉强度。  
(例)A2-70 表示抗拉强度的最小值为700N/mm<sup>2</sup>。  
钢分类为A2(奥氏体不锈钢)

M×P(粗牙螺纹)	A	E	B
2×0.4	3.8	2	1.5
2.5×0.45	4.5	2.5	2
2.6×0.45	4.5	2.6	2
3×0.5	5.5	3	2.5
4×0.7	7	4	3
5×0.8	8.5	5	4
6×1.0	10	6	5
8×1.25	13	8	6
10×1.5	16	10	8

【不锈钢型】

型号		l	型号		l
① 代码	② M-③ L		① 代码	② M-③ L	
EBSC (不锈钢)	2- 3	全螺 纹	EBSC (不锈钢)	3- 4	全螺 纹
	4			5	
	5			6	
	6			8	
	8			10	
	10			12	
	12	14		18	
	15	15			
		16			
	2.5- 4	全螺 纹		18	全螺 纹
	5			20	
	6			25	
	8			30	
	10			35	
	12			40	
15		4- 5	全螺 纹		
2.6- 4	全螺 纹	6			
5		8			
6		10			
8		12			
10		14			
12		15			
15		16			
		18			
		20			
	22				
	25				



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

**SRD 仕瑞达**