



垫圈/轴环/垫片

金属垫圈

精密级 内外径公差选择·尺寸自由指定型



1 型号 — 公差选择 — 2 D — 3 V — 4 D — 5 V — 6 T
 ECMC — N X — D10.0 — V4.0 — T1.0

■ 请按步骤 1~6 选择型号和参数后进行订购。




型号区分: 7 天发货
 代码



型号	材质	表面处理
ECMC	S45C	—
ECMB		发黑
ECMM		无电解镀锌
ECMS	SUS304	—

2 \sqrt{r} / (1.6/)



※D=16以下 C0.2以下
 D=16.5以上 C0.5以下

D	D公差选择			
	G	H	N	X
5.0~8.5	g6	h7	—	—
9.0~10.0	-0.005	0	-0.1	0
	-0.014	-0.015		
10.5~18.0	-0.006	0	-0.3	-0.2
	-0.017	-0.018		
18.5~30	-0.007	0	-0.3	-0.2
	-0.020	-0.021		
31~50	-0.009	0	-0.3	-0.2
	-0.025	-0.025		
51~60	-0.010	0	-0.3	-0.2
	-0.029	-0.030		

V	V公差选择			
	H	N	X	
3.0	+0.010	—	—	—
	0	—	—	—
3.5~6.0	+0.012	—	—	—
	0	—	—	—
6.5~10.0	+0.015	—	—	—
	0	—	—	—
10.5~18.0	+0.018	+0.3	+0.2	0
	0	+0.1	0	0
18.5~30.0	+0.021	—	—	—
	0	—	—	—
30.5~50.0	+0.025	—	—	—
	0	—	—	—
50.5~58.0	+0.030	—	—	—
	0	—	—	—

1 型号	2 D公差选择	3 V公差选择	4 D	5 V 最小单位 0.5mm	6 T 最小单位 0.1mm
ECMC ECMB ECMM ECMS	G H N X	H N X	5.0~10.0 单位0.5mm	3.0~58.0 (V≤D-2)	1.0~2.9
			10.5~20.0 单位0.5mm		3.0~5.0
			21~30 单位1mm		5.1~10.0
			31~40 单位1mm		1.0~2.9
			41~50 单位1mm		3.0~5.0
			51~60 单位1mm		5.1~10.0
					1.0~2.9
					3.0~5.0
					5.1~10.0
					1.0~2.9
					3.0~5.0
					5.1~10.0
					1.0~2.9
					3.0~5.0
					5.1~10.0

① D: V公差选择了G或H时, 适用D≥9。 * 材质SUS304 T≥3.1
 此时, V的指定范围如下表所示。


D	V	T
9~30	D-V≥6	1~10
31~60	D-V≥12	2~10



1 型号 — 公差选择 — 4 D — 5 V — 6 T — (TSB · TSC · TSD · TSE)

ECMC — G H — D10.0 — V4.0 — T1.0 — TSB

可加工	变更负公差	变更正公差	变更零·负公差	变更零·正公差
代码	TSB	TSC	TSD	TSE
变更精密级	变更厚度公差(T) -0.01 T -0.03	变更厚度公差(T) T +0.03 T +0.01	变更厚度公差(T) 0 T -0.02	变更厚度公差(T) T +0.02 0
公差	指定方法 TSB	指定方法 TSC	指定方法 TSD	指定方法 TSE



垫圈·轴环·垫片

