

直线轴承固定座组件 ▶ 直线轴承/滚珠导向组件



型号(1 代码· 2 d)
ADHB20

■ 请按步骤 1 ~ 2 选择型号和参数后进行订购。



型号区分: 7 天发货
代码

1 代码	内置直线轴承	固定座		使用环境温度
ADHB	ADMU	材质 铝合金	表面处理 本色阳极氧化	

1 代码	2 d	公差	L	L1	h	H	(H1)	(H2)	W	W1	W2	M	d	L	(A)	(B)
ADHB	6	0 - 0.009	25	15	9	18	15	6	30	20	5	M4	3.4	8	12	0.4
	8		30	18	11	22	18		34	24					16	
	10		35	21	13	26	21		40	28	6				15.5	
	12		36			28	24	8	42	30.5	5.75	M5	4.3	12	17.5	
	13		39	26	15	30	24.5		44	33	5.5				19	
	16	0 - 0.010	44	34	19	38.5	32.5	9	50	36					19.8	0.85
	20		50	40	21	41	35	11	54	40	7	M6	5.2		21	
	25		67	50	26	51.5	42	12	76	54	11				36	
	30		72	58	30	59.5	49	15	78	58	10	M8	7	18	39.9	0.75

2 d	基本额定负载		静态容许力矩 (N· m)	参考重量(g)
	C(动) N	Co(静)N		
5	167	206	-	14
6	206	265	-	34
8	265	380	-	52
10	372	549	-	92
12	412	598	-	102
13	510	784	-	120
16	775	1180	-	220
20	882	1370	-	255
25	980	1570	-	600
30	1570	2740	-	735
35	1670	3140	-	1100
40	2160	4020	-	1590
50	3820	7940	-	3340

国际单位1N = 0.102kgf

滚珠直线
导向轴承
组件

04



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达