







■ 平头螺栓止动型



代码		材质	表面处理	耐热温度
圆型	正方形			
EAHXC	EAHXS	钕磁铁	镀镍	80℃
EAHXCH	EAHXSH	耐热钕磁铁		150℃



磁化方向：厚度



① N极划线或点



型号 (① 代码 · ② A) — ③ T
EAHXC8 — 3

■ 请按步骤①~③选择型号和参数后进行订购。



型号区分：⑦ 天发货
代码

型号		① 代码	② A	③ T	d1	d2	附件	吸引力 N {kgf}				表面磁通密度高斯[G]			
								EAHXC	EAHXCH	EAHXS	EAHXSH	EAHXC	EAHXCH	EAHXS	EAHXSH
(圆型) EAHXC EAHXCH (正方形型) EAHXS EAHXSH	8	2	3	5.5	3	M2.5-6		7.8 {0.8}	7.8 {0.8}	10.8 {1.1}	—	2000~2500	2000~2500	3000~3400	—
								10.8 {1.1}	10.8 {1.1}	16.6 {1.7}	—	2400~2800	2400~2800	3200~3600	—
	10	3	4	6.5	3.5	M3-8		14.7 {1.5}	14.7 {1.5}	22.5 {2.3}	—	3500~4000	3500~4000	3000~3300	—
								18.6 {1.9}	18.6 {1.9}	24.5 {2.5}	24.5 {2.5}	4000~4200	4000~4200	3800~4000	3800~4000
	12	3	4.5	6.5	3.5	M3-8		18.6 {1.9}	—	—	—	3600~4000	—	—	—
								23.5 {2.4}	23.5 {2.4}	27.4 {2.8}	27.4 {2.8}	4100~4300	4100~4300	3900~4100	3900~4100
	15	4	5	9	4.8	M4-10		23.5 {2.4}	—	—	—	3800~4200	—	—	—
								41.1 {4.2}	41.1 {4.2}	54.8 {5.6}	54.8 {5.6}	4200~4500	4200~4500	4000~4300	4000~4300
	20	4	5.5	11	5.8	M5-12		49 {5.0}	—	—	—	3800~4100	—	—	—
								54.8 {5.6}	54.8 {5.6}	78.4 {8.0}	78.4 {8.0}	4200~4400	4200~4400	4000~4200	4000~4200
	25	4	6	13	7	M6-15		58.8 {6.0}	—	—	—	3700~4100	—	—	—
								78.4 {8.0}	78.4 {8.0}	98.0 {10.0}	98.0 {10.0}	4100~4400	4100~4400	3900~4300	3900~4300

