



无油衬套

无油衬套嵌入式法兰型固定座组件 内置铜合金衬套 单衬·双衬 标准型



型号 ①代码·②d)
MFIMS6
MFIMS-S6

■ 请按步骤①~②选择型号和参数后进行订购。




型号区分:
代码 7 天发货

■ 标准型




● 嵌入式单衬型




圆法兰型


A向视图



方法兰型




● 嵌入式双衬型



两面切割法兰型

d=6~13

d=16~30



型号				D		L				ℓ	H	T	d1	d2	t	P.C.D.	W	F	A		
① 代 码	②d	公 差	Da			单衬型	双衬型	加长型													
● 单衬型 (无密封圈) (带非接触式密封圈)	圆法兰型	方法兰型	两面切割法兰型	6	+0.022 0	12	0 -0.018	11.8	22	37	52	5	28	5	3.5	6	3.1	20	22	—	20
				8	+0.028 0	15		14.8	27	47	67		32				24	25	—	24	
				10		19		18.8					40				29	30	—	29	
				12		21	0	20.8	32	57	82	6	42	6	4.5	7.5	4.1	32	32	—	32
				13	+0.034 0	23	-0.021	22.8					43					33	34	—	33
				16		28		27.8	37	67	97		48					38	37	22	31
● 双衬型 (无密封圈) (带非接触式密封圈)				20		32	0	31.6	42	77	112	8	54	8	5.5	9	5.1	43	42	24	36
				25	+0.041 0	40	-0.025	39.6	58	108	158		62					51	50	32	40
				30		45		44.6	68	128	188	10	74	10	6.6	11	6.1	60	58	35	49
				35		52	0	51.6	68	128	—	10	82					67	64	—	—
				40	+0.050 0	60	-0.030	59.6	80	150	—	13	96	13	9	14	8.1	78	75	—	—
				50		80		79.6	90	170	—	13	116					98	92	—	—

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613