

铰链销

超短头内六角孔带肩螺帽固定型

悬臂销/铰链销/支点用台阶螺丝



D公差 (g6)	
4~6	-0.004 -0.012
8~10	-0.005 -0.014
12~18	-0.006 -0.017
20~25	-0.007 -0.020

代码	材质	硬度	表面处理	附件	
BDLBK	S45C	40~45HRC	发黑	螺帽1个	SWRCH
BDLBKH					SUS304
BDSL BK					SUS440C
BDSL BKH	SUS440C	45~50HRC	-		SUS304

$\sqrt[25]{(1.6/)}$

悬臂销・铰链销
支点用台阶螺丝

12


型号(①代码・②D) — ③L
 BDLBK15 — 120.3

■ 请按步骤①~③选择
型号和参数后进行订购。

型号区分: ④代码 7 天发货

型号		③L 最小单位 0.1mm	A	T	F	B	E	u	(n)	M (粗牙螺纹)					
① 代码	②D														
BDLBK BDLBKH BDSL BK BDSL BKH	4	10.0~ 50.0	7	1.5	6	2	2	3.9	1.5	M3					
	5	10.0~ 60.0	9		9	2.5		4.9		M4					
	6	10.0~100.0	10			3		5.8		M5					
	8		13		12			7.8		M6					
	10	15.0~100.0	16	2.5	16	4	3	9.8		M8					
	12	15.0~150.0	18		18	5		11.8		M10					
	13	25.0~150.0	24					12.8		M12					
	14							13.8							
	15							14.8							
	16							15.8							
	20	30.0~150.0	27		24	6	4	19.8		M16					
	25		30			8	5	24.8							

型号(①代码・②D) — ③L — (FC...etc.)
 BDLBK10 — 50.5 — FC8

	变更螺纹部长度	变更螺纹直径	变更L尺寸公差	加工肩部止转面																		
可选加工																						
代码	FC	MC	LKC	HC																		
技术说明	指定方法 FC4 ① FC = 最小单位1mm ② M(MC) ≤ FC ≤ M(MC) × 3	指定方法 MC3 <table border="1"><thead><tr><th>D</th><th>MC选择范围</th></tr></thead><tbody><tr><td>5</td><td>3</td></tr><tr><td>6</td><td>3 4</td></tr><tr><td>8</td><td>3 4 5</td></tr><tr><td>10</td><td>4 5 6</td></tr><tr><td>12</td><td>5 6 8</td></tr><tr><td>13~16</td><td>6 8 10</td></tr><tr><td>20</td><td>8 10 12</td></tr><tr><td>25</td><td>10 12</td></tr></tbody></table> ① 选择D12、MC5时, 请同时使用加工 FC。 ⓧ D4不适用	D	MC选择范围	5	3	6	3 4	8	3 4 5	10	4 5 6	12	5 6 8	13~16	6 8 10	20	8 10 12	25	10 12	指定方法 LKC 变更L尺寸公差为 ±0.05。	指定方法 HC ・ D = 4~10 HC = A/2 - 1 ・ D = 12~25 HC = A/2 - 2
	D	MC选择范围																				
5	3																					
6	3 4																					
8	3 4 5																					
10	4 5 6																					
12	5 6 8																					
13~16	6 8 10																					
20	8 10 12																					
25	10 12																					



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRO仕瑞达