






型号
BADR20





型号区分：
代码 **5** 天发货





BADR (轴台型)



BADRCP (简易轴台型)



BADB (底部安装型)



精度: JIS B 1558
JIS B 1514
JIS B 1559
轴承箱轴承座直径的精度: H7(间隙配合)
使用温度: -15~+100℃

构成零件	材质
①固定座	FC200
②轴承	SUJ2
③橡胶密封圈	丁腈橡胶(NBR)
④止动螺丝	SCM435

型号	JIS公称规格	H		L		L ₁						t		H ₁				基本额定负载 (kN)		止动螺丝			重量 (g)			
代码	D	BADR	BADR	BADB	BADR	BADB	BADR	BADB	A	d ₁	d	M	ℓ	BADR	BADB	BADR	BADB	B	S	Cr(动)	Cor(静)	M ₁	紧固扭矩 (N·cm)	轴向负载 能力 (N)	BADR	BADB
BADR BADB	12	UCP201																						650	550	
	15	UCP202	30.2	30.2	127	76	95	52	38	19	13	M10×1.5	12	15	8	62	62	31.0	12.7	12.8	6.6	M6×0.75	392	640	630	530
	17	UCP203																						620	520	
	20	UCP204	33.3													65								1280	650	500
	25	UCP205	36.5	36.5	140	84	105	56		16			15	16	10	70	72	34.1	14.3	14.0	7.9	M8×1	490	1400	790	720
	30	UCP206	42.9	42.9	165	94	121	66		18	18		18	18		83	84	38.1	15.9	19.6	11.3			1960	1260	1020
	35	UCP207	47.6	47.6	167	110	127	80	48	21			20	19		94	95	42.9	17.5	25.9	15.4			2590	1590	1580
	40	UCP208	49.2	49.2	184	116	137	84		25	17	M14×2.0	20	19	12	100	100			29.3	17.9	M10×1.25	1180	2930	1920	1840
	45	UCP209	54.0	54.2	190	120	146	90		22			20			108	108	49.2		33.0	20.5			3300	2190	2060
	50	UCP210	57.2	57.2	206	130	159	94	60	25	20	M16×2.0	22	14	114	116	51.6		35.5	23.2			3550	2590	2440	

型号		H	L	L ₁	A	d ₁	d	t	H ₁	B	S	基本额定负载 (kN)		止动螺丝			重量 (g)
代码	D											Cr (动)	Cor (静)	M ₁	紧固扭矩 (N · cm)	轴向负载能力 (N)	
BADRCP (无注油嘴)	12	30.2	114	87	25	16	12	12	57	22.0	6	9.55	4.8	M5×0.8	240	476	390
	15																380
	17																360
	20	33.3	125	97	27	13	64	24.7	7	12.8	6.6	250	1280	480			
	25	36.5	130	100	29		70	27.0	7.5	14.0	7.9	M6×0.75	490	1400	590		
	30	42.9	156	120	33		21	14	15	83	30.3			8	19.6	11.3	1960



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRO仕瑞达