



轴承、轴承座组件

滚珠轴承组件 铸铁法兰型





型号
BADH20





型号区分: 5 天发货
代码





BADH (菱形法兰型)



BADHCP (简易菱形法兰型)



BADF (方法兰型)



精度: JIS B 1558
JIS B 1514
JIS B 1559
轴承箱轴承座直径的精度: H7(间隙配合)
使用温度: -15~+100℃

构成零件	材质
①固定座	FC200
②轴承	SUJ2
③橡胶密封圈	丁腈橡胶(NBR)
④止动螺丝	SCM435

型号		JIS公称规格			基本额定负载 (kN)																止动螺丝				重量 (g)			
代码	D	BADH	BADF	F	F ₁	W	L	L ₁	t	A	A ₁	A ₂	d	d ₁	B	S	Cr (动)	Cor (静)	M ₁	紧固扭矩 (N · cm)	轴向负载 能力 (N)	BADH	BADF					
BADH BADF	12	UCFL201	UCF201	113	90	60	86	64	12	33.3	25.5	15	12	12	31.0	12.7	12.8	6.6	M6×0.75	392	640	470	630					
	15	UCFL202	UCF202																			450	610					
	17	UCFL203	UCF203																			440	600					
	20	UCFL204	UCF204																			1280	420	580				
	25	UCFL205	UCF205	130	99	68	95	70	14	35.8	27.0	16	16	14	34.1	14.3	14.0	7.9	M8×1	1180	1400	590	720					
	30	UCFL206	UCF206	148	117	80	108	83		40.2	31.0	18			38.1	15.9	19.6	11.3			1960	900	1010					
	35	UCFL207	UCF207	161	130	90	117	92		44.4	34	19			42.9	17.5	25.9	15.4			2590	1200	1380					
	40	UCFL208	UCF208	175	144	100	130	102		51.2	36	21	16	16	49.2	19	29.3	17.9			2930	1510	1770					
	45	UCFL209	UCF209	188	148	108	137	105	18	52.2	38	22					33.0	20.5	M10×1.25	2350	3550	3300	1900	2070				
	50	UCFL210	UCF210	197	157	115	143	111		54.6	40						35.5	23.2				3550	2200	2360				

型号													基本额定负载 (kN)		止动螺丝			重量 (g)
代码	D	F	F ₁	W	t	A	A ₁	A ₂	d	B	S	Cr (动)	Cor (静)	M ₁	紧固扭矩 (N · cm)	轴向负载 能力 (N)		
BADHCP (无注油嘴)	12																280	
	15	81	63.5	56	9.5	25.5	18	9.5	7	22	6	9.55	4.8	M5×0.8	250	476	270	
	17																250	
	20	90	71.5	63		28.7	20		11	10		24.7	7				12.8	6.6
	25	95	76	69	11	30.5	20.0					27	7.5	14.0	7.9	M6×0.75	490	1400
30	113	90.5	79	12	34.3	22.5	12	12	30.3	8	19.6	11.3			1960			580

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613