



型号(①代码·②D) — ③L  
EATP5 — 10

■请按步骤①~③选择型号和参数后进行订购。




型号区分:  
代码 **7** 天发货

### ■一端螺纹型



代码	材质	硬度
EATP	SUU2	58HRC~
EATPC	SUS440C	58HRC~
EATPCS	SUS304	-



通气槽深度



l <sub>1</sub>	M×P	l	型号		③L										
			①代码	②D											
1.5	3×0.5	6	EATP EATPC	5	10	15	20	25	30						
	4×0.7	*8		6	10	15	20	25	30	35	40	50			
2.0	5×0.8	10		8	15	20	25	30	35	40	45	50	60	70	80
	6×1.0			10	10	15	20	25	30	35	40	45	50	60	70
2.5	8×1.25	15		12	20	30	40	50	60	70	80				
				13	40	50	60	70	80						
3.0			16	40	50	60	70								


l <sub>1</sub>	M×P	l	型号		③L										
			①代码	②D											
1.5	3×0.5	6	EATPC	5	10	15	20								
	4×0.7	*8		6	15	20	25	30							
2.0	5×0.8	10		8	15	20	25	30	35	40					
	6×1.0			10	10	20	25	30	35	40	45	50	60		
2.5	8×1.25	15		12	30	40	50	60							
				13	30	40	50	60							

l <sub>1</sub>	M×P	l	型号		③L									
			①代码	②D										
1.5	3×0.5	6	EATPCS	5	10	15	20	25	30					
	4×0.7	*8		6	10	15	20	25	30	35	40			
2.0	5×0.8	10		8	15	20	25	30	35	40	45	50		

### ■一端螺纹型(通孔)



代码	材质	硬度
EAHS	SUU2	45~50HRC
EAHSS	SUS440C	



l <sub>1</sub>	l <sub>2</sub>	M×P	l	Dp6	型号		③L							
					①代码	②D								
2	0.3	4×0.7	8	+0.020 +0.012	EAHS	6	15	20	25	30	35			
		5×0.8		+0.024 +0.015		8	15	20	25	30	35			
2.5	1.0	6×1.0	10	+0.029 +0.018		10	20	25	30	35	40	45		
				12	20	25	30	35	40	45				

l <sub>1</sub>	l <sub>2</sub>	M×P	l	Dp6	型号		③L							
					①代码	②D								
2	0.3	4×0.7	8	+0.020 +0.012	EAHSS	6	15	20	25	30	35			
		5×0.8		+0.024 +0.015		8	15	20	25	30	35			
2.5	1.0	6×1.0	10	+0.029 +0.018		10	20	25	30	35	40	45		
				12	20	25	30	35	40	45				

