



1 型号 — 2 T公差选择 — 3 D — 4 V — 5 T
 ECWB — B — D20.0 — V8.0 — T5.0

■ 请按步骤 1~5 选择型号和参数后进行订购。



型号区分: 7 天发货
 代码

型号	材质	表面处理	硬度
ECWC	S45C	—	—
ECWB		发黑	
ECWM		无电解镀锌	
ECWS	SUS304	—	45~50HRC
ECWH	SUS440C	—	

T尺寸公差选择表			
B	-0.1	SB	-0.01
	-0.3		-0.03
C	+0.3	SC	+0.03
	+0.1		+0.01
D	0	SD	0
	-0.2		-0.02
E	+0.2	SE	+0.02
	0		0

$\sqrt{25} \left(\frac{1.6}{\sqrt{\quad}} \right)$
 ※D=16以下 C0.2以下
 D=16.5以上 C0.5以下

1 型号	2 T公差选择	3 D	4 V 最小单位0.5mm	5 T 最小单位 0.1mm
ECWC ECWB ECWM ECWS ECWH	—普通级— B C D E	5.0~10.0 单位0.5mm	3.0~58.0	1.0~ 2.9
		10.5~20.0 单位0.5mm		3.0~ 5.0
		21~30 单位1mm		5.1~10.0
		31~40 单位1mm		1.0~ 2.9
		41~50 单位1mm		3.0~ 5.0
		51~60 单位1mm		5.1~10.0
	—精密级— SB SC SD SE	31~40 单位1mm		1.0~ 2.9
		41~50 单位1mm		3.0~ 5.0
		51~60 单位1mm		5.1~10.0
		1.0~ 2.9		
		3.0~ 5.0		
		5.1~10.0		

① V≤D-2 * 材质SUS304(精密级) T≥3.1

