



型号(代码·M)  
EBSTRC8



型号区分: 代码 5 天发货

■紧凑型螺帽

材 质 SUS304  
※强度分类 EBSTRC 5T  
EBSTRCS 4T

型号		(粗牙)螺距	B	(e)	T	T <sub>1</sub>
代码	M					
EBSTRC EBSTRCS (薄型)	4	0.7	6	6.9	2.4	2
	5	0.8	7	8.1	3.2	2.5
	6	1	8	9.2	3.6	3
	8	1.25	10	11.5	5	4
	10	1.5	13	15	6	4.5
	12	1.75	17	19.6	7	5.5

■加高螺帽

代码	材质	表面处理	硬度
EBT	S45C	光泽镀锌	25~30HRC
EBST	SUS304	-	-

型号		H	B	(C)	D <sub>1</sub>
代码	M (粗牙螺纹)				
EBT EBST	6	9	10	11.5	9.8
	8	12	13	15	12.5
	10	15	17	19.6	16.5
	12	18	19	21.9	18
	16	24	24	27.7	23
	20	30	30	34.6	29
24	36	36	41.6	34	



型号(①代码·②M) — ③L ■请按步骤①~③选择型号和参数后进行订购。

EBTFL5

— 15



型号区分: 代码 7 天发货

■全长指定螺帽

代码	材质	表面处理
EBTFL	SS400	无电解镀锌
EBTFLS	SUS304	-

■L尺寸选择型

型号		③L	B	(C)	D <sub>1</sub>
①代码	②M (粗牙螺纹)				
EBTFL EBTFLS	3	4 5 6 8 10	6	6.9	5.3
	4	5 6 8 10 12 15	7	8.1	6.8
	5	6 8 10 12 15 20	8	9.2	7.8
	6	10 12 15 20 25	10	11.5	9.8
	8	10 15 20 25 30	13	15	12.5
10	10 20 25 30 40	17	19.6	16.5	

■L尺寸指定型

型号		③L 最小单位1mm	B	(C)	D <sub>1</sub>
①代码	②M (粗牙螺纹)				
EBTFL EBTFLS	3	3~10	6	6.9	5.3
	4	4~15	7	8.1	6.8
	5	5~20	8	9.2	7.8
	6	6~25	10	11.5	9.8
	8	8~30	13	15	12.5
	10	10~40	17	19.6	16.5
12	10~50	19	21.9	18	
16	10~50	24	27.7	23	



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达