



开口型

① $D^{+0.05}_{-0.01}$ 为线切割加工前的公差。

代 码	材质	表面处理	附件
ACD	S45C	发黑	1个内六角螺栓(SCM435)
ACPD		无电解镀锌	1个内六角螺栓(不锈钢)
ACSD	SUS304	—	

分离型

代 码	材质	表面处理	附件
ACSPD	S45C	发黑	2个内六角螺栓(SCM435)
ACPPD		无电解镀锌	2个内六角螺栓(不锈钢)
ACSSPD	SUS304	—	

25/(6.3/)



① 代码 ② D
ACD15

■ 请按步骤①~②选择型号和参数后进行订购。



型号区分: 7 天发货

型号		B	D ₁	B ₁	t	M (粗牙螺纹)	d	H	C	X	(Z)	Y	(W)
①代 码	②D												
(开口型) ACD ACPD ACSD	3	10	15	8	2	M3	3.4	6	0.5	4.5	5	3	1
	4										6		
	5	12	20	10	M4	4.5	7.5	6		7	4		
	6									6.5			
	8	18	30	15	3	M6	7	12		9	10	5	1.5
	10		35							10	12.5	6	
12	11												
15	40		13						13	8			
16	20		15						15		10		
(分离型) ACSPD ACPPD ACSSPD	20	45	22	5	M8	9	14	18	18	12		2	
25	50	20						20					
30	55	23						21					
35	60	26						23	13				
40	23	70						18	M10	11	18		32
50	27	85	22										

① ACD的D尺寸公差为+0.01~+0.08°



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达