



定位导向零件

调整螺栓用固定块

标准型・侧面安装型



型号 (1 代码 · 2 No.) — 3 H
DBJKC6 — 8

■ 请按步骤 ①～③ 选择型号和参数后进行订购。



型号区分: 7 天发货
代码

■标准型



代码	材质	表面处理
DBJKC	S45C	发黑
DBJKCM		无电解镀镍
DBJKCS	SUS304	—



定位导向零件


21

型号		③H选择			d	H ₁	T	W	P	d ₂	d ₁	ℓ
① 代码	② No.											
DBJKC DBJKCM DBJKCS (No.3—10)	3	5	10	15	2.5	5	7	26	16	3.5	6	3.5
	4	5	10	15 20	3.5							
	5	6	10	15 20 25	4.5	6	9	32	20	4.5	8	4.5
	6	8	10	15 20 25 30	5.5							
	8	10	15 20 25 30		7.5	8	12	38	26	5.5	9.5	5.5
	10		12 15 20 25 30		9.5	10	16	50	32			
	12		12 15 20 25 30		11.5					9	14	9
	16		15 20 25 30		15.5	11	19	65	40			

■侧面安装型




代码	材质	表面处理
DBJSC	S45C	发黑
DBJSCM		无电解镀镍
DBJSCS	SUS304	—




型号		③H选择			d	H ₁	T	W	P	H ₂	d ₁
① 代码	② No.										
DBJSC DBJSCM DBJSCS (No.3—10)	3	15	20		2.5	5	7	26	16	4	4
	4	15	20		3.5						
	5	15	20 25		4.5	6	9	32	20	5	6
	6	15	20 25 30		5.5						
	8	20	25 30 40		7.5	8	12	38	26	6	7
	10		25 30 40		9.5	10	16	50	32	9	9.5
	12		25 30 40		11.5						
	16		25 30 40		15.5	11	19	65	40	12	11.5

■侧面安装 T尺寸紧凑型



代码	材质	表面处理
DBJSCC	S45C	发黑
DBJSCCS	SUS304	—



型号		③H选择			d	H ₁	T	W	P	H ₂	d ₁
① 代码	② No.										
DBJSCC DBJSCCS	4	15	20		3.5	5	3	25	16	4	4
	5	15	20 25		4.5						
	6	15	20 25 30		5.5	6	5	32	20	5	6
	8	20	25 30 40		7.5	8		38	26	6	7

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613