



型号(①代码·②M)  
FCPFUC18  
FCPFA14



型号区分: ①代码 ②天发货

形状	代码				材质	硬度	表面处理
	标准级		两平面				
	标准	薄型	标准	薄型			
标准型用	FCPFA	FCPFUA	FCPFC	FCPFUC	S45C	45~50HRC	发黑
	FCPFAS	FCPFUAS	FCPFCs	FCPFUCs	SUS440C		—
紧凑型用	FCPUA	—	FCPUC	FCPUUC	S45C		发黑

25/(6.3/)

■浮动接头(标准型用)挡板

型号		A	P.C.D.	E	G	K	
①代码	②No. 对应M						
标准级 标准 薄型 FCPFA FCPFUA FCPFAS FCPFUAS	3	42	30	24	30	4.5	
	4						
	5	48	34	28	34	6	
	6						
	8	51	37	30	37	7	
	10						
	12	70	52	42	52	10	
	14						
	两平面 标准 薄型 FCPFC FCPFUC FCPFCs FCPFUCs	16	90	68	54	68	12
		18					
20		106	80	66	80	14	
22							
24		116	86	78	86	14	
26							
30		134	104	80	104	18	

①No.对应浮动接头 法兰安装型的M。 ②挡板的No.30适用于M36的浮动接头。 ③薄型M3、M4不可选。

■浮动接头(紧凑型用)挡板

型号		A	P.C.D.	E	K
①代码	②No. 对应M				
标准级 标准 FCPUA	5	34	24	22	4.5
	6				
	8	40	30	25	6
	10				
	12	52	40	34	7
	14				
两平面 标准 薄型 FCPUC FCPUUC	16	62	48	41	10
	18				
	20	74	58	48	10
	22				
	24	80	64	54	10
	26				
	30	90	74	64	64



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达