



型号(①代码·②轮数量)

CCOP

■ 请按步骤①~②选择型号和参数后进行订购。



型号区分:

代码



7 天发货

■ 压制轮



滚轮种类	安装螺帽种类	轮距	材质			表面处		
		P=35 无支架型	①滚轮	轴承	②型材	③螺丝·螺帽	①滚轮	②型材
压制轮	普通螺帽 (JIS3种)	CCOP	钢			镀锌		

① 聚氨酯的硬度为肖氏A90黑色。



* 槽宽尺寸为 $5.2^{+1.2}$ 。(适用M5螺柱)

■ 每个滚轮的耐负载

滚轮的材质	耐负载
压制	15kgf(147N)

代码	h	d	W	t
CCOP	29.7	25.4	10	1.6

型号		(L)
代码	轮数量	P=35
	2	(68)
	3	(103)
	4	(138)
	5	(173)
	6	(208)
	7	(243)
	8	(278)
	9	(313)
	10	(348)
	11	(383)
	12	(418)
	13	(453)
	14	(488)
	15	(523)
	16	(558)
	17	(593)
	18	(628)
	19	(663)
	20	(698)
	21	(733)
	22	(768)
	23	(803)
	24	(838)
	25	(873)
	26	(908)
	27	(943)
	28	(978)
	29	(1013)
	30	(1048)
	31	(1083)
	32	(1118)
	33	(1153)

■ 压制轮
CCOP
(钢制)



型号 - (cc)
CCOP30 - CC

可选加工	代码	技术说明
CC 	CC	变更型材边长的倒角尺寸。 指定方法 CC
将C3变更为C8		

① 压制轮的每个滚轮的承载能力为15kgf(147N)。



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达