



平皮带/圆皮带/滑轮/惰轮

平皮带用惰轮 宽度T=25~100

轴承压入型·轴承拆卸型



■ 请按步骤①~③选择型号和参数后进行订购。

型号(①代码·②D) - ③d - ④L - ⑤H - ⑥X - ⑦Y - ⑧Z

圆弧形 CDFAC60 - 20 - L75 - H0.5

带肋槽直柱型 CDFAM60 - 20 - L75 - X14.0 - Y11.8 - Z5.0



型号区分: 7天发货

■ 轴承压入型

直杆型
CDFAN

圆弧形
CDFAC

带肋槽直柱型
CDFAM

肋槽部

材 质 铝合金
表面处理 本色阳极氧化处理
①轴承采用压入方式。无法拆卸。

型号		③d	最小单位1mm ④L	仅圆弧形 可选 ⑤H	仅带肋槽直柱型 最小单位0.1mm			d ₁	轴承尺寸																																																									
① 代码	② D				⑥ X	⑦ Y	⑧ Z		No.	D ₁	B																																																							
直杆型 CDFAN 带肋槽直柱型 CDFAM 圆弧形 CDFAC	15	5	直杆型 圆弧形 25~100 带肋槽直柱型 50~100 ① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	7	675ZZ	8	2.5																																																							
		9						678ZZ	10	3																																																								
	20	6						① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	10	686ZZ	13	5																																																		
		8											678ZZ	12	3.5																																																			
	25	6											① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	10	696ZZ	15	5																																													
		8																688ZZ	16	5																																														
	30	10																① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	15	6900ZZ	22	6																																								
		12																					698ZZ	19	6																																									
	35	10																					① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	17	6900ZZ	22	6																																			
		12																										6901ZZ	24	6																																				
	40	15																										① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	17	6902ZZ	28	7																														
		12																															628ZZ	24	8																															
	50	10																															① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	17	6000ZZ	26	8																									
		15																																				6901ZZ	24	6																										
	60	12																																				① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	17	6902ZZ	28	7																				
		15																																									620ZZ	30	9																					
	80	25																																									① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	22	6001ZZ	30	8															
		30																																														6902ZZ	28	7																
	35	12																																														① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	27	6904ZZ	37	9										
		15																																																			6905ZZ	42	9											
	40A	25																																																			① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	22	6201ZZ	32	10					
		30																																																								6002ZZ	32	9						
	45	25																																																								① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	32	6904ZZ	37	9
		30																																																													6905ZZ	42	9	
50	25	① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	32																																																								6906ZZ	47	9	
	30						6205ZZ																																																								52	15		
60	25						① L ≥ B × 2 + 2	0.3 0.5 0.8	7.0~15.0	5.0~12.0	2.0~4.5	41																																																			6006ZZ	55	13	
	35											6907ZZ																																																			55	10		

■ 轴承拆卸型

代码	材质	表面处理	材质 轴承
CDFB	S45C	发黑	钢
CDFM		无电解镀镍	
CDFA	铝合金	本色阳极氧化处理	

① 轴承可拆卸。

6.3 (1.5/)

D=30A·40A

型号		④L 选择	d	d ₁	轴承尺寸								
① 代码	② D				No.	D ₁	B	C	h				
CDFB CDFM CDFA	20	38	6	15	F696ZZ×2	15	5		17				
		45			F606ZZ×2	17	6	1.2	19				
	30	38			8	22	698ZZ×2	19					
		45					F608ZZ×2	22	7	1.5	25		
	40A	38					10	17	6000ZZ×2	26	8		
		45											

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613