








BA6□□□ZCC3

● 径向间隙 单位: μm

轴承内径 d (mm)	CN		C3	
	最小	最大	最小	最大
10	2	13	8	23
12	3	18	11	25
15	5	20	13	28
18	5	20	13	28
20	6	20	15	33
22	6	23	18	36

材 质 SUJ2
轴承精度 GB 307 P0
JIS B 1514 0级



型号
BA6000ZCC3



型号区分: **5** 天发货
交货期

型号	d	D	B	r (min.)	基本额定负载		容许转速 rpm (参考)	安装尺寸				重量 (g) (参考)
					Cr (动) kN	Co (静) kN		Ds		dh (max.)	R (max.)	
BA6000ZCC3	10	26	8	0.3	4.55	1.97	30000	12	13	24	0.3	18
BA6300ZCC3		35	11	0.6	8.1	3.45	22000	14	16.5	31	0.6	52
BA6001ZCC3	12	28	8	0.3	5.1	2.37	28000	14	15.5	26	0.3	22
BA6201ZCC3		32	10	0.6	6.8	3.05	22000	16	17	28	0.6	37
BA6301ZCC3		37	12	1	9.7	4.2	20000	17	18	32	1	60
BA6002ZCC3	15	32	9	0.3	5.6	2.83	24000	17	19	30	0.3	31
BA6202ZCC3		35	11	0.6	7.65	3.75	20000	19	20.5	31	0.6	45
BA6003ZCC3	17	35	10	0.3	6	3.25	22000	19	21.5	33	0.3	41
BA6203ZCC3		40	12	0.6	9.55	4.8	17000	21	23.5	36	0.6	67
BA6004ZCC3	20	42	12	0.6	9.4	5	18000	24	25.5	38	0.6	68
BA6204ZCC3		47	14	1	12.8	6.6	15000	25	26.5	42	1	107
BA6304ZCC3		52	15	1.1	15.9	7.9	14000	26.5	28	45.5	1	145
BA6005ZCC3	25	47	12	0.6	10.1	5.85	15000	29	30	43	0.6	79
BA6205ZCC3		52	15	1	14	7.85	13000	30	32	47	1	129
BA6006ZCC3	30	55	13	1	13.2	8.3	13000	35	36.5	50	1	116
BA6206ZCC3		62	16	1	19.5	11.3	11000	35	38.5	57	1	199
BA6007ZCC3	35	62	14	1	16	10.3	11000	40	41.5	57	1	151

