



型号(①代码·②D) — ③L
EASTM6 — 20

■请按步骤①~③选择型号和参数后进行订购。




型号区分: ④
代码 7 天发货

■一端螺纹型(公差p6·m6)




代码	D公差	材质	硬度
EAST	p6	SUJ2	45~50HRC
EASTM	m6		


EAST



EASTM




通气槽深度



l ₁	l ₂	M×P	l	Dp6	型号		③L
					①代码	②D	
1.5	0.5	3×0.5	*6	+0.020 +0.012	EAST (P6型)	5	10 15 20 25 30
		4×0.7	*8			6	10 15 20 25 30 35 40 50
5×0.8			8	15 20 25 30 35 40 45 50 60 70 80			
6×1.0	10	+0.024 +0.015	10	15 20 25 30 35 40 45 50 60 70 80			
2.0	1.0	8×1.25	15	+0.029 +0.018		12	20 30 40 50 60 70 80
						13	40 50 60 70 80
2.5	1.0	10×1.5	18	+0.035 +0.022		16	40 50 60 70 80
						20	50 60 70 80

l ₁	l ₂	M×P	l	Dm6	型号		③L
					①代码	②D	
1.5	0.3	3×0.5	*6	+0.012 +0.004	EASTM (M6型)	5	10 15 20 25 30
		4×0.7	*8			6	10 15 20 25 30 35 40 50
5×0.8		+0.015 +0.006	8	15 20 25 30 35 40 45 50 60 70 80			
6×1.0	10		10	15 20 25 30 35 40 45 50 60 70 80			
2.0	0.5	8×1.25	15	+0.018 +0.007		12	20 30 40 50 60 70 80
						13	40 50 60 70 80
2.5	1.0	10×1.5	18	+0.021 +0.008		16	40 50 60 70 80
						20	50 60 70 80

■锥形螺纹型



代码		材质	硬度
EAMT		SK4	45~50HRC

M×P	l	型号		③L
		①代码	②D	
EAMT	5×0.8	9	8	30 40
	6×1.0	10	10	40 50
	8×1.25	14	12	40 50
	10×1.5	16	13	50 60
				16



邮箱: Service@srdfaa.com



传真: 0755-8957-5523