



型号(①代码·②D) — ③L  
**EASCM4** — 12  
**EASV2** — 6

■请按步骤①~③选择型号和参数后进行订购。



型号区分: **7** 天发货  
 代码

### 直杆型 倒角C型



| C         | 型号    |     | ③L |   |    |    |    |    |    |
|-----------|-------|-----|----|---|----|----|----|----|----|
|           | ① 代码  | ② D |    |   |    |    |    |    |    |
| 0.3<br>以下 | EASCM | 2   | 6  | 8 | 10 | 12 | 15 |    |    |
|           |       | 3   |    |   | 10 | 12 | 15 | 20 |    |
|           |       | 4   |    |   | 10 | 12 | 15 | 20 |    |
|           |       | 5   |    |   | 10 | 12 | 15 | 20 |    |
| 0.5       |       | 6   |    |   | 10 | 12 | 15 | 20 | 25 |

| 代码            | 材质      | 硬度     |
|---------------|---------|--------|
| <b>EASCM</b>  | SUS440C | 58HRC~ |
| <b>EASCSM</b> | SUS304  | -      |




| C         | 型号     |     | ③L |   |    |    |    |    |    |
|-----------|--------|-----|----|---|----|----|----|----|----|
|           | ① 代码   | ② D |    |   |    |    |    |    |    |
| 0.3<br>以下 | EASCSM | 2   | 6  | 8 | 10 | 12 | 15 |    |    |
|           |        | 3   |    |   | 10 | 12 | 15 | 20 |    |
|           |        | 4   |    |   | 10 | 12 | 15 | 20 |    |
|           |        | 5   |    |   | 10 | 12 | 15 | 20 |    |
| 0.5       |        | 6   |    |   | 10 | 12 | 15 | 20 | 25 |

### 直杆 高精度型



| l1 | l2  | 型号   |     | ③L |    |    |    |    |    |    |
|----|-----|------|-----|----|----|----|----|----|----|----|
|    |     | ① 代码 | ② D |    |    |    |    |    |    |    |
| 1  | 0.2 | EASV | 2   | 6  | 8  | 10 |    |    |    |    |
|    |     |      | 3   |    | 8  | 10 | 15 | 20 | 25 | 30 |
| 4  |     |      | 10  | 15 | 20 | 25 | 30 |    |    |    |
| 5  |     |      | 10  | 15 | 20 | 25 | 30 |    |    |    |
| 6  |     |      | 10  | 15 | 20 | 25 | 30 |    |    |    |
| 8  |     |      |     |    |    | 20 | 30 | 40 |    |    |
| 2  | 0.5 | 10   |     |    |    | 30 | 40 | 50 | 60 |    |
| 3  |     |      |     |    |    |    |    |    |    |    |

| 代码           | 材质      | 硬度     |
|--------------|---------|--------|
| <b>EASV</b>  | SUJ2    | 58HRC~ |
| <b>EASVC</b> | SUS440C | 58HRC~ |



| l1  | l2  | 型号    |     | ③L |    |    |    |    |    |    |
|-----|-----|-------|-----|----|----|----|----|----|----|----|
|     |     | ① 代码  | ② D |    |    |    |    |    |    |    |
| 0.4 | 0.1 | EASVC | 1   | 5  | 6  | 8  | 10 |    |    |    |
| 0.6 |     |       | 1.5 | 5  | 6  | 8  | 10 |    |    |    |
| 1   | 0.2 |       | 2   | 5  | 6  | 8  | 10 |    |    |    |
|     |     |       | 3   |    | 6  | 8  | 10 | 15 | 20 | 25 |
| 1.5 | 0.5 |       | 4   |    | 8  | 10 | 15 | 20 | 25 | 30 |
| 2   |     |       | 5   |    | 10 | 15 | 20 | 25 | 30 |    |
| 2.5 |     | 6     |     | 10 | 15 | 20 | 25 | 30 |    |    |
| 3   |     | 8     |     |    |    | 20 | 30 | 40 |    |    |
|     |     | 10    |     |    |    |    | 30 | 40 | 50 | 60 |



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

**SRD 仕瑞达**