



轴承、轴承座组件

角接触球轴承 单列·两列组合型

■ 角接触球轴承
单列·两列组合型

单列
BA7000□
BA720□

BA700□-DB
BA720□-DB

两列组合型
BA700□-DF
BA720□-DF

(安装图)

以上几款为接触角度30°

轴承精度 GB 307 P5
JIS B 1514 5级

材质 SUJ2

型号

BA7000
BA7000-DB

交货期

型号区分: **5** 天发货

■ 单列型

型号	d	D	B	r (min.)	r1 (min.)	基本额定负载		容许转速 rpm (参考)	作用点 a	安装尺寸			重量 (g) (参考)
						Cr (动) kN	Cor (静) kN			Ds (min.)	dh (max.)	R (max.)	
BA7000	10	26	8	0.3	0.15	5.35	2.6	23200	9.2	12.5	23.5	0.3	23
BA7200		30	9	0.6	0.3	5.4	2.71	22400	10.3	15	25	0.6	29
BA7001	12	28	8	0.3	0.15	5.8	2.98	20800	9.8	14.5	25.5	0.3	25
BA7201		10	6	0.3	0.3	8	4.05	20000	11.4	17	27	0.6	37
BA7002	15	32	9	0.3	0.15	6.1	3.45	18400	11.3	17.5	29.5	0.3	35
BA7202		11	6	0.3	0.3	8.65	4.65	17600	12.7	20	30	0.6	46
BA7003	17	35	10	0.3	0.15	6.4	3.8	16800	12.5	19.5	32.5	0.3	46
BA7203		40	12	0.6	0.3	10.8	6	15200	14.2	22	35	0.6	67
BA7004	20	42	12	0.6	0.3	10.8	6.6	14400	14.9	25	37	0.6	80
BA7204		14	1	0.6	0.6	14.5	8.3	13600	16.7	26	41	1.0	109
BA7005	25	47	12	0.6	0.3	11.3	7.4	12800	16.4	30	42	0.6	93
BA7205		52	15	1	0.6	16.2	10.3	11200	18.6	31	46	1.0	130
BA7006	30	55	13	1	0.6	14.5	10.1	10400	18.8	36	49	1.0	135
BA7206		62	16	1	0.6	22.5	14.8	9600	21.3	36	56	1.0	197

■ 两列组合型

型号		d	D	B	r (min.)	r1 (min.)	基本额定负载		容许转速 rpm (参考)	作用点a		安装尺寸						重量 (g) (参考)
							Cr (动) kN	Cor (静) kN		DB	DF	DB			DF			
轴承型号	两列组合型											Ds (min.)	dh (max.)	R (max.)	Ds (min.)	dh (max.)	R (max.)	
BA7000	DB (背面)	10	26	8	0.3	0.15	8.75	5.2	18400	18.4	2.4	12.5	24.8	0.3	11.2	23.5	0.15	46
BA7200			30	9	0.6	0.3	8.8	5.4	17600	20.5	2.5	15	27.5	0.6	12.5	25	0.3	58
BA7001		12	28	8	0.3	0.15	9.4	5.95	16800	19.5	3.5	14.5	26.8	0.3	13.2	25.5	0.15	50
BA7201			10	6	0.3	0.3	13	8.05	16000	22.7	2.7	17	29.5	0.6	14.5	27	0.3	74
BA7002		15	32	9	0.3	0.15	9.95	6.85	14400	22.6	4.6	17.5	30.8	0.3	16.2	29.5	0.15	70
BA7202			11	6	0.3	0.3	14	9.3	13600	25.4	3.4	20	32.5	0.6	17.5	30	0.3	92
BA7003		17	35	10	0.3	0.15	10.4	7.65	13600	25	5	19.5	33.8	0.3	18.2	32.5	0.15	92
BA7203			40	12	0.6	0.3	17.6	12	12000	28.5	4.5	22	37.5	0.6	19.5	35	0.3	134
BA7004		20	42	12	0.6	0.3	17.6	13.2	12000	29.9	5.9	25	39.5	0.6	22.5	37	0.3	160
BA7204			14	1	0.6	0.6	23.5	16.6	10400	33.3	5.3	26	42	1	25	41	0.6	218
BA7005		25	47	12	0.6	0.3	18.3	14.8	9600	32.8	8.8	30	44.5	0.6	27.5	42	0.3	186
BA7205			52	15	1	0.6	26.3	20.5	8800	37.2	7.2	31	47	1	30	46	0.6	260
BA7006	55	13	23.6	20.2			8800	37.5	11.5	6	50	1	35	49	0.6	270		
BA7206	62	16	36.5	29.5			7840	42.6	10.6	36	57	1	56	56	0.6	394		
BA7207	DB (背面)	35	72	17	1.1	48.5	40	6800	47.9	—	42	67	1	—	—	—	574	
BA7208		40	80	18		57.5	50.5	6000	52.6	—	47	75	1	—	—	—	750	
BA7209		45	85	19		64.5	57.5	5520	56.5	—	52	80	1	—	—	—	822	

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613