







■ 平头螺栓止动型  
表面S级上型



代码		材质	表面处理	耐热温度	磁级	
圆型	正方形型				表面	反面
EAHXCW	EAHXSW	钕磁铁	镀镍	80℃	S	N



磁化方向：厚度



① N极划线或点



型号 (1 代码 · 2 A) — (3 T)  
EAHXC8 — 3

■ 请按步骤 ①~③ 选择型号和参数后进行订购。



型号区分：7 天发货

型号	① 代码	② A	③ T	d1	d2	附件	吸引力 N {kgf}		表面磁通密度高斯[G]		紧固扭矩 (N.m)
							EAHXCW	EAHXSW	EAHXCW	EAHXSW	
(圆型) EAHXCW	8	2	3	5.5	3	M2.5-6	7.8 {0.8}	10.8 {1.1}	2000~2500	3000~3400	0.8
							10.8 {1.1}	16.6 {1.7}	2400~2800	3200~3600	
	10	3	4	6.5	3.5	M3-8	14.7 {1.5}	22.5 {2.3}	3500~4000	3000~3300	1.5
							18.6 {1.9}	24.5 {2.5}	4000~4200	3800~4000	
(正方形型) EAHXSW	12	3	4.5	6.5	3.5	M3-8	18.6 {1.9}	—	3600~4000	—	1.5
							23.5 {2.4}	27.4 {2.8}	4100~4300	3900~4100	
	15	3	5	9	4.8	M4-10	23.5 {2.4}	—	3800~4200	—	3.6
							41.1 {4.2}	54.8 {5.6}	4200~4500	4000~4300	
	20	4	5.5	11	5.8	M5-12	49 {5.0}	—	3800~4100	—	7.6
							54.8 {5.6}	78.4 {8.0}	4200~4400	4000~4200	
25	4	6	13	7	M6-15	58.8 {6.0}	—	3700~4100	—	13	
						78.4 {8.0}	98.0 {10.0}	4100~4400	3900~4300		

备注：紧固扭矩若超出上表值，将导致磁铁开裂。



邮箱：Service@srdfaa.com



传真：0755-8957-5523

SRD仕瑞达