



联轴器

链条联轴器



(1)②③套件
(仅①链条)
(仅②壳体)

型号(①代码·②No.)

CAPC4012
CACH3012
CABH6022

③d1 — ④d2
— 14 — 16

■请按步骤①~④选择型号和参数后进行订购。
轴孔径请在 $d_1 \leq d_2$ 的范围内指定。



型号区分:

代码

10 天发货

■链条联轴器




①链条+③主体




②壳体

名称	代码	材质			附件
		①链条	②壳体	③主体	
套件①+②+③	CAPC	钢	铝合金压铸	S45C(齿顶高频淬火)	固定螺丝
链条①	CACH	钢	—	—	—
壳体②	CABH	—	铝合金压铸	—	固定螺丝


链条①
(No.=3512)




(No.4012~6022)



套件(①+②+③)



■轴孔规格
(新JIS键+螺纹孔)



*的轴孔直径止动螺丝位于此处。

■套件

型号		③d1、④d2选择 (但d1≤d2)										重量 (kg)	D	E	F	G	L ₁	ℓ ₁	ℓ ₂	C	最高转速 (r/min)	50rpm以下的 容许传递扭矩 (N·m)
① 代码	②No.																					
CAPC (①+②+③)	3012	14*	16*									0.6	69	25	26.5	45	64.8	29.8	16	10.2	250	100
	4012	14	15	16	17	18	19	20	22*			0.9	77	33	36	62	79.4	36	17	14.4	250	218
	4014	17	18	19	20	22	24	25	28*	30*		1.2	84	43	45	69	79.4	36	17	14.4	200	296
	4016	19	20	22	24	25	28	30	32			1.7	92	48	51	77	87.4	40	23	14.4	200	386
	5014	20	22	24	25	28	30	32	35			2.3	101	53	56	86	99.7	45	24	18.1	150	563
	5016	22	24	25	28	30	32	35	38	40		3.1	111	60	63	96	99.7	45	24	18.1	150	735
	5018	30	32	35	38	40	42	45				3.8	122	70	73	106	99.7	45	24	18.1	150	931
	6018	40	42	45	48	50	55					7.0	142	85	88	127	123.5	56	28	22.8	100	1,754
	6022	48	50	55								11.7	168	110	115	152	123.5	56	28	22.8	100	2,372

■单品

型号		仅链条						
①代码	②No.	链数	P	H	H ₁	B	Y	重量 (kg)
CACH (仅①链条)	3012	12	9.525	8.1	8.1	23.85	5.72	0.1
	4012	12	12.70	10.41	12.06	32.78	7.90	0.2
	4014	14	12.70	10.41	12.06	32.78	7.90	0.2
	4016	16	12.70	10.41	12.06	32.78	7.90	0.3
	5014	14	15.875	13.01	15.08	41.45	9.54	0.4
	5016	16	15.875	13.01	15.08	41.45	9.54	0.5
	5018	18	15.875	13.01	15.08	41.45	9.54	0.6
	6018	18	19.05	15.64	18.09	52.30	12.7	1.0
	6022	22	19.05	15.64	18.09	52.30	12.7	1.3

■键槽尺寸表

轴孔直径 d1·d2	键槽 b2×t2	固定螺丝 M
14~17	5×2.3	6
18~22	6×2.8	6
24~30	8×3.3	8
32~38	10×3.3	8
40~42	12×3.3	8
45~50	14×3.8	10
55	16×4.3	12

■安装容差

- 角度误差 $\alpha = 0.5^\circ$ 以下
- 平行误差 ϵ = 链条节距的1%以下

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613