




■加厚型





代码	材质	表面处理	附件
ABSSTBN	S45C	发黑	1个内六角螺栓
ABSSTMN		无电解镀锌	1个内六角螺栓(SUS)

① D尺寸30~50有2个附属螺栓。

① 安装孔D按容差H7加工后，进行开口加工。有可能因加工增至H8左右。

●D8~25

●D30~50

 $\frac{25}{\sqrt{6.3}} \frac{1.6}{\sqrt{1.6}}$ 

① 代码 ② D — ③ H
ABSSTMN20 — 30

■请按步骤①~③选择型号和参数后进行订购。



型号区分：

代码

7 天发货

型号		高度选择						L	H ₁	T	S	W	L ₁	d	E	d ₂	d ₁	ℓ	C	紧固螺栓 M		
① 代码	② D																				③ H	
ABSSTBN ABSSTMN	8	10	15	20	25	30	40	48	H+18	15	6	24	36	6.6	11	6.6	11	6.5	2	M6通孔		
	10	10	15	20	25	30	40	50	60	48	H+19	15	6	24	36	6.6	12	6.6	11		6.5	2
	12	10	15	20	25	30	40	50	60	48	H+21	18	6	24	36	6.6	14	6.6	11		6.5	2
	13	15	20	25	30	40	50	60	48	H+21	18	6	24	36	6.6	14	6.6	11	6.5		2	
	15	15	20	25	30	40	50	60	54	H+23	20	6	30	42	6.6	16	6.6	11	6.5		2	
	16	15	20	25	30	40	50	60	54	H+23	20	6	30	42	6.6	16	6.6	11	6.5		2	
	20	20	25	30	40	50	60	80	67	H+29	25	8	35	50	9	19	9	14	9	2	M8通孔	
	25	20	25	30	40	50	60	80	67	H+31	30	8	35	50	9	22	9	14	9	2		
	30	25	30	40	50	60	80	85	H+33	35	10	45	65	6.6	24	9	14	9	3			
	35	25	30	40	50	60	80	85	H+36	35	10	45	65	6.6	27	9	14	9	3			
	40	30	40	50	60	80	100	H+38	40	10	60	80	9	29	9	14	9	3				
	50	40	50	60	80	125	H+51	50	15	75	100	11	38	14	20	13	3	M12深度24				

