



同步轮/同步带/免键轴衬


免键轴衬 简易型(带定心功能)





型号(代码 · d)
CBLR10



型号区分: **7** 天发货
代码



CBLR
CBLRP
(无电解镀镍)
CBLRS
(不锈钢)



代码	主体	
	材质	表面处理
CBLR	S45C	—
CBLRP	S45C	无电解镀镍
CBLRS	SUS304	—

■轴及轮孔部的推荐公差、表面粗糙度

安装面	公差	表面粗糙度
轴外径	h7(g6)	Ra1.6以下
轮孔部内径	H7	Ra3.2以下

型号		D	D ₁	P.C.D.	T	B	锁紧螺栓		重量 (g)
代码	d						M×L	个数	
CBLR CBLRP (无电解镀镍)	5	12	23	15.5	9	10	M3×8	4	36
	6	15	28	19.5	11	12	M4×10	4	61
	8	18	31.5	22.5	11	12	M4×10	5	78
	10	20	33.5	24.5	11	12	M4×10	5	86
	12	22	35.5	26.5	11	12	M4×10	5	94
	14	23	38.5	28.5	13	14	M5×12	4	135
	15	24	39.5	29.5	13	14	M5×12	4	140
	16	25	40.5	30.5	13	14	M5×12	4	146
	17	26	46	33	14	16	M6×14	4	221
	18	27	47	34	14	16	M6×14	4	228
	19	28	48	35	14	16	M6×14	4	235
	20	32	52	39	16	20	M6×14	4	287
	22	34	54	41	16	20	M6×14	4	302
	24	39	59	46	20	22	M6×14	4	293
	25	41	61	48	20	22	M6×14	4	378
	28	43	63	50	22	24	M6×14	4	396
	30	47	67	54	22	24	M6×14	4	414
	32	53	73	60	25	30	M8×18	8	484
	35	59	84	69	25	30	M8×18	8	560
	40	65	90	75	25	30	M8×18	8	962
	50								1090

d	CBLR · CBLRP			CBLRS		
	容许最大扭矩 (N · m)	容许轴向 负载 (kN)	螺栓紧固 扭矩 (N · m)	容许最大扭矩 (N · m)	容许轴向 负载 (kN)	螺栓紧固 扭矩 (N · m)
5	9	3.45	1.7	3	1.05	1.1
6	11			4		
8	25	6.09	4.0	8	2.75	2.7
10	44			14		
12	53	8.71	8.0	17	5.00	5.6
14	61			20		
15	115	15.30	14.0	38	7.40	9.6
16	123			41		
17	131	23.20	34.80	43	11.10	14.90
18	210			68		
19	221	34.80	46.40	71	27.50	23.6
20	233			75		
22	256	46.40	84.50	83		
24	279			90		
25	291	84.50	34.0	94		
28	488			157		
30	523	84.50	34.0	168		
32	558			180		
35	813	84.50	34.0	262		
40	929			299		
45	1910	84.50	34.0	620		
50	2120			690		

国际单位1N=0.102kgf

同步轮·同步带
免键轴衬

15

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613