



螺丝/螺帽

台阶螺栓 超短头型·短头型



型号 (1) 代码 · (2) M — (3) L — (4) F
EBDGS6 — 3 — 10

■ 请按步骤 ①~④ 选择型号和参数后进行订购。



型号区分: 7 天发货



■ 超短头型



代码	材质	表面处理
EBDGB	S45C	发黑
EBDGM	S45C	无电解镀锌
EBDGS	SUS303	—

参考值(并非保证值)

M	拉伸断裂负载
M3	1950
M5	4630



型号		最小单位 1mm		E	D	A	B	ℓ	h1
① 代码	② M(粗牙螺纹)	③ L	④ F						
EBDGB EBDGM EBDGS	3	5~20	3~6	1.5	5	8	1.5	1	1.5
	4		4~8		6	10	2	1.2	2
	5		5~10		8	12	3	1.4	3
	6		6~12		10	16	3	1.5	3
	8		8~12		12	18	4	1.5	3.5
	10		10~15		15	20	5	1.5	4



■ 短头型



代码	材质	表面处理
EBDTB	S45C	发黑
EBDTM	S45C	无电解镀锌
EBDTS	SUS303	—

参考值(并非保证值)

M	拉伸断裂负载
M3	1950
M5	4630



型号		最小单位 1mm		E	D	A	B	ℓ	h1
① 代码	② M(粗牙螺纹)	③ L	④ F						
EBDTB EBDTM EBDTS	3	3~20	3~6	2	5	8	2	1	2
	4		4~8	2.8	6	10	2.5	1.2	2.5
	5		5~10	3.5	8	12	3	1.4	3
	6		6~12	4	10	16	4	1.5	3.5
	8		8~12	5	12	18	5	1.5	4
	10		10~15	6	15	20	6	1.5	4.5




型号 (1) 代码 · (2) M — (3) L — (4) F — (LTC · PC)
EBDTB6 — 3.4 — 10 — LTC

可选加工


代码

可选加工



LTC

变更L尺寸最小单位 LTC=最小单位 0.1mm



PC

对M尺寸部进行根部退刀槽加工。

D	M×螺距	g	f
5	M3×0.5	1	2.3
6	M4×0.7	1.2	3.2
8	M5×0.8	1.4	4.0
10	M6×1.0	1.7	4.8
12	M8×1.25	2	6.5
15	M10×1.5	2	8.2

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613