




型号 (① 代码 · ② No.)
STWP4-9

■ 请按步骤 ① ~ ② 选择型号和参数后进行订购。




型号区分: 5 天发货
代码



■ C型挡圈(孔用)



EARWN
EARWS (不锈钢)



适用孔



代码	材质	硬度
EARWN	弹簧钢	44~53HRC
EARWS	SUS304—CSP	36~44HRC

型号		挡圈							参考	适用孔 (参考)					
代码	No.	d3	公差	t	公差	b (约)	a (约)	d0 (最小)	d4	d1	d2	公差	m	公差	n (最小)
EARWN EARWS (不锈钢)	10	10.7	±0.18	1	±0.05	1.5	2.8	1.2	4	10	10.4	+0.11 0	1.15	+0.14 0	1.5
	11	11.8					3		4	11	11.4				
	12	13					3.1		5	12	12.5				
	13	14.1				1.7	3.1	1.5	6	13	13.6				
	14	15.1					3.6		7	14	14.6				
	15	16.2				1.9	3.6	1.7	8	15	15.7				
	16	17.3	3.7				8		16	16.8					
	17	18.3	3.8				9		17	17.8					
	19	20.5	2.5			4	2	11	19	20	+0.21 0	1.35			
	20	21.5				4		12	20	21					
	21	22.5				4.1		12	21	22					
	22	23.5				4.1		13	22	23					
	24	25.9				4.3		15	24	25.2					
	25	26.9	3	4.4	16	25		26.2	+0.25 0	1.65					
	26	27.9		4.6	16	26		27.2							
	28	30.1		4.6	18	28		29.4							
	30	32.1		4.7	20	30		31.4							
	32	34.4		3.5	5.2	21		32			33.7				
	35	37.8	5.2		24	35		37							
	37	39.8	5.2		26	37		39							
	40	43.5	±0.4	1.75	±0.07	4	5.7	2.5	28		40	42.5	+0.3 0	1.9	
	42	45.5					5.8		30	42	44.5				
	45	48.5					5.9		33	45	47.5				
	47	50.5				4.5	6.1		34	47	49.5				
	52	56.2					6.5		39	52	55				
	55	59.2	5.5			6.5	41		55	58	+0.35 0	2.2			
	60	64.2				6.8	46		60	63					
	62	66.2				6.9	48		62	65					
68	72.5	7.4				53	68		71						
72	76.5	7.4				57	72		75						
80	85.5	±0.55	2.5			±0.08	7		8	64	80		83.5	+0.35 0	2.7

