

止动螺丝型/开口型 避空键槽型

固定环






1 代码 2 D — 3 B
ACKS12 — 10
ACPKS10 — 10

■ 请按步骤 1~3 选择型号和参数后进行订购。



型号区分: 7 天发货
代码

止动螺丝型






型号		B 选择		D1	d1	止动螺丝 M×长度	C	b	Z
1 代码	2 D								
ACKS ACPKS	10	6	8 10	20	13	M4×3	0.5	3.5	7
	12		8 10	22	15	M5×4		4.5	8.5
	15		8 10 12	26	20			5.5	10.5
	20		10 12	32	27	M6×5		6.5	13.5
	25		12 15	38	31	M6×5	1	8.5	16.5
	30		15 20	46	38	M8×6		8.5	19.0

开口型



① D₁+0.05/-0.01为线切割加工前的公差。



型号		B 选择	D ₁	M (粗牙螺纹)	d	R	W	C	X	Y	Z	b			
① 代 码	② D														
ACSKS ACPSKS	10	10	30	M4	4.5	3.75	1.5	0.5	9	5	7	3.5			
		12		M5	5.5	4.5			10	6					
		15	35	M6	6.6	6				5	8.5	4.5			
	12	10	30	M4	4.5	3.75			11	6			10.5	5.5	
		12		M5	5.5	4.5					12	8			
		15	35	M6	6.6	6						13			7
	15	10	34	M4	4.5	3.75			11.5	6	14	7	16.5	8.5	
		12	35	M5	5.5	4.5						15			8
		15	40	M6	6.6	6									17
	20	10		40	M5	5.5			4.5	14	7	13.5			6.5
		12	M6		6.6	6			15		8				
		15	45	M5	5.5	4.5			17	7	16.5	8.5			
	25	12	45	M6	6.6	6			18	10			19		
		15		50	M6	6.6					6	1		20	
		30	55												



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达