



带座轴承

轴承、轴承座组件


无挡圈双轴承嵌入型L尺寸选择型



■ 圆型




■ 方型




■ 简易型

d3~17



d20~30

 $\frac{63}{\sqrt{16}}$ 型号(1)代码·(2)轴承型号·(3)密封圈) — (4)L
BBAHY628ZZ — 35■ 请按步骤①~④选择
型号和参数后进行订购。

型号区分:

代码

7 天发货

型号			L 选择	S	d	DH7	公差	B	H	W	T	dh	D197	公差	P.C.D.	K	A	F	d1	d2	H1	可订购型号			
① 代码	② 轴承型号	③ 密封圈																				BBFYB BBFY BBAFY BBSAFY BBSFY	BBKYB BBKY BBAKY BBSAKY BBSKY	BBHYB BBHY BBAHY BBSAHY BBSHY	—
(圆型)	623	ZZ (双盖式)	20 30	5	3	10	+0.015 0	4	33	16	7	7	14	-0.006 -0.024	24	27	24	—	6.5	3.5	3.1	●	●	●	—
	624		20 30	5	4	13	+0.018 0	5	35	18		9	17	26	28	26	●					●	●	—	
	605		25 35	5	14	5		38	20	10		18	28	30	28	●	●					●	—		
	625		35 40	10	5	16		5	40	22		12	20	30	31	30	●					●	●	—	
	606		25 40	5	17	6		41	23	13		21	-0.007 -0.028	31	32	31	●					●	●	—	
	626		35 45	10	6	19	+0.021 0	6	44	25		15	24	34	34	34	●					●	●	—	
	678		20 30	5	12	+0.018 0	3.5	35	18	10		16	-0.006 -0.024	26	28	26	●					●	●	—	
	698		25 35	5	19	6	44	25	15	24		34	34	34	34	34	●					●	●	—	
	608		25 35	5	22	+0.021 0	7	47	29	18		27	37	36	37	●	●					●	—		
	628		35 45	10	24	8	50	32	20	30		-0.007 -0.028	40	37	40	●	●					●	—		
6700	20 30	5	15	+0.018 0	4	40	22	12	19	30	31	30	●	●	●	—									
6800	20 30	5	19	5	44	25	15	24	34	34	34	34	●	●	●	—									
6900	25 40	5	22	+0.021 0	6	47	29	19	27	37	36	37	●	●	●	—									
6000	35 50	10	26	0	8	52	34	22	32	-0.009 -0.034	42	39	42	●	●	●	—								
6200	45 55	15	30	9	56	38	24	36	-0.034	46	42	46	●	●	●	—									
6701	20 30	5	18	+0.018 0	4	44	25	15	23	34	34	34	●	●	●	—									
6801	25 35	5	21	5	47	29	17	26	-0.007 -0.028	37	36	37	●	●	●	—									
6901	35 50	10	24	+0.021 0	6	50	31	21	30	40	38	40	●	●	●	—									
6001	35 50	10	28	8	54	36	24	34	-0.009 -0.034	44	40	44	●	●	●	—									
6201	45 55	15	32	+0.025 0	10	58	40	26	38	48	43	48	●	●	●	—									
6702	25 35	10	21	+0.021 0	4	47	29	18	26	-0.007 -0.028	37	36	37	●	●	●	—								
6802	25 35	10	24	5	50	32	20	30	-0.028	40	37	40	●	●	●	—									
6902	35 60	10	27	7	59	37	25	35	47	45	47	47	●	●	●	—									
6002	45 65	15	32	+0.025 0	9	62	40	28	38	50	46	50	●	●	●	—									
6202	50 65	15	35	0	11	66	44	29	42	54	49	54	●	●	●	—									
6803	30 40	10	26	+0.021 0	5	52	34	22	32	42	39	42	●	●	●	—									
6903	45 55	15	30	0	7	60	38	27	36	48	46	48	●	●	●	—									
6003	50 65	15	35	+0.025 0	10	66	44	31	42	-0.009 -0.034	54	50	54	●	●	●	—								
6203	60 70	20	40	0	12	72	50	34	48	60	54	60	●	●	●	—									
6704	30 40	10	27	+0.021 0	4	59	35	23	33	47	45	41	23	8	4.5	4.1	●	●	●	—					
6804	35 50	10	32	7	62	40	28	38	50	46	44	24	9.5	5.5	5.1	●	●	●	—						
6904	50 65	15	37	9	72	47	34	45	59	54	54	24	●	●	●	—									
6004	60 70	20	42	12	77	54	36	50	64	59	56	32	●	●	●	—									
6204	65 70	20	47	+0.025 0	14	81	58	40	54	-0.010 -0.040	68	62	59	34	11	6.6	6.1	●	●	●	—				
6805	35 50	15	37	7	72	47	34	45	-0.009 -0.034	59	54	54	24	●	●	●	—								
6905	35 50	15	42	9	77	54	36	50	-0.034	64	59	55	32	●	●	●	—								
6005	60 80	20	47	+0.030 0	12	88	58	41	54	-0.010 -0.040	72	67	63	36	14	9	8.1	●	●	●	—				
6205	65 80	20	52	+0.030 0	15	94	64	45	60	-0.040	78	72	68	39	14	9	8.1	●	●	●	—				
6806	35 50	15	42	+0.025 0	7	77	54	11	36	-0.009 -0.034	64	59	56	32	11	6.6	6.1	●	●	●	—				
6906	35 50	15	47	9	88	58	41	54	72	67	62	36	●	●	●	—									
6006	60 80	20	55	13	96	66	48	62	-0.010 -0.040	80	73	70	40	14	9	8.1	●	●	●	—					
6206	70 80	20	62	16	104	74	55	70	-0.040	88	79	77	44	●	●	●	—								
6007	70 80	20	62	14	104	74	55	70	88	79	75	44	●	●	●	—									
6207	70 90	20	72	+0.030 0	17	126	88	20	64	84	74	—	-0.012 -0.047	105	95	92	51	17.5	11	11	●	●	●	—	
6008	80 90	25	68	15	114	82	13	60	78	-0.010 -0.040	96	86	80	54	14	9	8.1	●	●	●	—				
6208	70 90	20	80	18	134	96	74	92	74	92	—	—	-0.012 -0.047	113	102	98	56	17.5	11	11	●	●	●	—	
6010	80 90	20	80	16	134	96	74	92	74	92	—	—	-0.012 -0.047	113	—	98	56	17.5	11	11	●	●	●	—	
6210	100	20	90	+0.035 0	20	147	110	83	106	126	—	—	—	126	—	104	72	—	—	—	●	●	●	—	

型号(1)代码·(2)轴承型号·(3)密封圈) — (4)L — (NA)
BBAKY6000ZZ — 35 — NA

可加工

代码

技术说明

不装配轴承

NA

不将轴承装入固定座中，而以附件形式发货。



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达