

浮动接头 简易连接型

【内螺纹】气缸连接件 尺寸指定型

气缸/相关配件



型号 (1) 代码 · (2) M—螺距 — (3) T — (4) L
 FCJRL4—0.7 — 8 — 20
 FCJGF4—0.7 — 4.5 — 15

■ 请按步骤 ①~④ 选择 型号和参数后进行订购。



型号区分: 代码 **7** 天发货

■ FCJRL

■ FCJGF

代码	材质	表面处理	表面硬度
FCJRL	S45C	镀硬铬	50HRC~
FCJGF	S45C	镀硬铬	50HRC~

$\frac{25}{\sqrt{6.3}}$

■ T选择/L指定型

① 代码	② M—螺距	③ T 选择											④ L 最小单位1mm	h	D	B	C
		2	3	4	5	6	8	9	10	12	13	15					
FCJRL	3~0.5	2	3	4	5	6							3~50	3	6	8	9.2
	4~0.7	2	3	4	5	6	8					3~60	7		10	11.5	
	5~0.8	3	4	5	6	8	9	10				3~60	8		12	13.9	
	6~1.0	3	4	5	6	8	9	10	12				4~80	10	14	16.2	
	8~1.0	4 5 6 8 9 10 12 13 15 16											4~100	4	13	17	19.6
	8~1.25	4 5 6 8 9 10 12 13 15 16 19 20											4~100		16	21	24.2
	10~1.25	4 5 6 8 9 10 12 13 15 16 19 20											5~100		18	23	26.6
	10~1.5	5 6 8 9 10 12 13 15 16 19 20													21	26	30
	12~1.25	5 6 8 9 10 12 13 15 16 19 20													8~100	25	30
	14~1.5	8 9 10 12 13 15 16 19 20											8~100		5	25	30
	16~1.5	8 9 10 12 13 15 16 19 20											8~100	27		32	36.9
	18~1.5	8 9 10 12 13 15 16 19 20											8~100				
22~1.5	12 15 20											10~100	6	27	32	36.9	

■ T/L指定型

① 代码	② M—螺距	③ T	④ L	h	D	B	C	
		最小单位0.1mm	最小单位1mm					
FCJGF	3~0.5	2.0~20.0	3~10	3	6	8	9.2	
	4~0.7	2.0~20.0	3~20		7	10	11.5	
	5~0.8	2.0~20.0	3~20		8	12	13.9	
	6~1.0	3.0~20.0	4~30	4	10	14	16.2	
	8~1.0	3.0~20.0	4~30		13	17	19.6	
	8~1.25	3.0~20.0	4~30		16	16	21	24.2
	10~1.25	3.0~20.0	4~40			18	23	26.6
	10~1.5	3.0~20.0	4~40				21	26
	12~1.25	4.0~20.0	5~40		5	25	30	34.6
	12~1.5	4.0~20.0	5~40	25		30	34.6	
	14~1.5	4.0~20.0	5~40			27	32	36.9
	16~1.5	8.0~30.0	8~40	6	27	32	36.9	
18~1.5	8.0~30.0	8~40						
22~1.5	10.0~30.0	10~40						

■ 平板连接时连接件T尺寸指定示例

单位: mm

加工法	板厚	公差		连接件T尺寸	间隙量*
		上限	下限		
例1 冷轧	4.5	0	-0.1	4.5	0.05~0.2
例2 热轧	5	+0.3	-0.3	5.3	0.05~0.7

*平板与连接件公差量的间隙

① h+T+L≤3M时, 螺纹孔变为通孔。

② FCJGF是气缸专用的浮动接头。



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达