




法兰一体型无油衬套 / 无油铜合金垫片




■ 请按步骤①~③选择型号和参数后进行订购。




■ 嵌入式法兰·中间法兰型



嵌入式法兰型




中间法兰型





圆法兰型

AFIZ (嵌入式法兰型)
AFCZ (中间法兰型)



两面切割法兰型

AFITZ (嵌入式法兰型)
AFCTZ (中间法兰型)




材质 高强度黄铜
合金类 镶嵌
石墨
附件 短头内六角螺栓
2~4根

型号			L	D _{h7}	D _a	L ₁	H	T	t	d ₁	d ₂	P.C.D.	F	A	附件 短头内六角螺栓	
① 代 码	② df7															
嵌入式法兰型	8	+0.028	20 25	12	0 -0.018	5	27	4	2.2	3.5	6	19	—	19	M3—10×2	
	10	+0.013	25 30	14			29					21				
	12		25 30	18			36					26				
	AFIZ AFITZ	13	+0.034	25 30 35	19	0 -0.021	6	37	5	3	4.5	7.5	27	27	26	M4—12×2
16		+0.016	25 30 35 40	22	40			30					18		24	
20			30 35 40 50	28	49			38					22		31	
中间法兰型		25	+0.041	30 35 40 50 60	33	0 -0.025	8	54	6	3.7	5.5	9	43	25	35	M5—16×4
	30	+0.020	35 40 50 60 70	38	63			50					30		40	
	35		50 70	44	69			56					36		43	
	AFCZ AFCTZ	40	+0.050	60 70 80	50	0 -0.030	10	82	8	4.2	6.6	11	66	38	54	M6—20×4
40		+0.025	70 100	62	94			78					50		60	
50				60	100			88					50		60	

■平头螺栓型




AFWZ (平头螺栓型)



■短头螺栓型



AFWTZ(短头螺栓型)



材质 高强度黄铜合金类 镶嵌石墨

型式		T	公差	D	公差	D ₁	安装孔						倒角	
代 码	No.						P.C.D.	数量	AFWZ 平头螺栓		AFWZ _t		a	b
								d ₁	d ₂	t				
AFWZ AFWZT	6	3(4)	0 -0.1	6.2	+0.2 +0.1	25	15	M3	3.5	6	2.4	1.5	0.3	
	8			28		18								
	10			30		20								
	12			40		28								
	13			13.2										
	15			15.2										
	16	5	18.2	50	35	2	4.5		7.5	3	2.5	0.4		
	18		18.2											
	20		20.2											
	25		25.2											
	30		30.2											
	35		35.2											
	40		40.2											
	7		80					60					M6	5.5
8	100	75	4	4	0.6									

* AFWZT No.6—18的T尺寸均1内数值。

* 平头螺栓为推荐尺寸。

* AFWTZ No.6~18的T尺寸为()内数值。

*平头螺栓为推荐尺寸。