



小零件/磁铁

油嘴/钢珠



型号
EAGPA6A

■ 请按步骤选择型号和参数后进行订购。



型号区分：
代码 **5** 天发货

■ 油嘴





图1

代码	材质	表面处理
EAGPA EAGPAS	黄铜 SUS303	镀镍 —




EAGPB



材 质 黄铜
表面处理 镀镍



EAGPC



材 质 黄铜
表面处理 镀镍

型号	No.	d	H	L	B
EAGPA EAGPAS	6	M6×P0.75	13.5	5	7
	6A	M6×P1.0	13.5	5	7
	1	R(PT)1/8	20	9	10
	2	R(PT)1/4	25	12	14

型号	No.	d	H	L	E	B
EAGPB	6	M6×P0.75	16.5	5	10	8
	6A	M6×P1.0	16.5	5	10	8
	1	R(PT)1/8	21.5	8	12.5	10
	2	R(PT)1/4	25	11	14.2	14

型号	No.	d	H	L	E	B
EAGPC	6	M6×P0.75	17.5	5	10.2	8
	6A	M6×P1.0	17.5	5	10.2	8
	1	R(PT)1/8	21.5	8	12.5	10
	2	R(PT)1/4	25	11	14.2	14



型号(①代码·②No.)
EABMJ3

■ 请按步骤①~②选择型号和参数后进行订购。




型号区分：
代码 **7** 天发货

■ 钢珠



EABIJ(英寸)
EABIS(英寸)
EABMJ(毫米)
EABMS(毫米)



* 28等级标准(JIS B1501) μm

直径偏差	max.	0.7
圆球度	max.	0.7
表面粗糙度	max.	0.05
一批产品相互 间直径误差	max.	1.4

代码	尺寸	材质	等级	硬度	标准
EABIJ	英寸	SUJ2	28	61~67HRC	JIS B1501
EABIS	英寸	SUS440C		59~66HRC	JIS B1501
EABMJ	毫米	SUJ2		61~67HRC	JIS B1501
EABMS	毫米	SUS440C		59~66HRC	JIS B1501

■ 英制

型号	No.	SD (英寸)
EABIJ EABIS	8	1/8
	10	5/32
	12	3/16
	14	7/32
	15	15/64
	16	1/4
	17	17/64
	18	9/32
	20	5/16
	22	11/32
	24	3/8
	26	13/32

■ 米制

型号	No.	SD (mm)
EABMJ EABMS	3	3
	3.5	3.5
	4	4
	4.5	4.5
	5	5
	6	6
	8	8

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613