



型号(1代码·2D) - (3M) - (4T)  
 ECAB12 - 6 - 5  
 ECFAM-D20 - M5 - T4.5

■ 请按步骤1~4选择型号和参数后进行订购。



型号区分: 7 天发货

T尺寸选择型	T尺寸指定型	尺寸自由指定型	材质	表面处理
-	-	ECFAC	S45C	-
ECAB	ECTAB	ECFAB		发黑
ECAM	ECTAM	ECFAM		无电解镀锌
-	-	ECFAA	铝合金	阳极氧化处理(本色)
ECAS	ECTAS	ECFAS	SUS304	-

M	螺距
2	0.4
2.6	0.45
3	0.5
4	0.7
5	0.8
6	1.0
8	1.25
10	1.5
12	1.75
16	2.0
20	2.5
24	3.0
30	3.5

### ■ T尺寸选择型

型号	2D	3M 选择				4T 选择			
1 代码		2	3	4	5	3	5	8	10
ECAB ECAM ECAS	10	2	3	4	5	3	5	8	10
	12			4	5	6	5	8	10
	16			5	6	8	5	8	10
	20			6	8	10	8	10	15
	30			8	10	12	10	15	20
	40			10	12	16	10	15	20
	50			16	20		15	20	
	60			16	20		15	20	

### ■ T尺寸指定型

型号	2D	3M 选择				4T
1 代码		2	3	4	5	最小单位 0.5mm
ECTAB ECTAM ECTAS	6	2	3	4		3.0~20.0
	8	2	3	4		
	10	2	3	4	5	
	12		4	5	6	3.5~20.0
	16		5	6	8	
	20		6	8	10	
	30		8	10	12	

① T ≤ M × 8 ② M2 → T ≤ M × 5

### ■ 尺寸自由指定型

型号	2D	3M 选择	4T 最小单位 0.5mm
1 代码			
ECFAC ECFAB ECFAM ECFAA ECFAS	6~10 (单位0.5mm)		3.0~5.0
			5.5~10.0
			10.5~20.0
			20.5~30.0
			30.5~40.0
			40.5~50.0
	10.5~20.0 (单位0.5mm)		3.0~5.0
			5.5~10.0
			10.5~20.0
			20.5~30.0
			30.5~40.0
			40.5~50.0
	21~30 (单位1mm)		2(3 ≤ T ≤ 10)
			2.6(3 ≤ T ≤ 13)
			3(3 ≤ T ≤ 24)
			4(3 ≤ T ≤ 32)
			5(3 ≤ T ≤ 40)
			6(3 ≤ T ≤ 48)
	31~40 (单位1mm)		8(4 ≤ T ≤ 50)
			10(5 ≤ T ≤ 50)
			12(6 ≤ T ≤ 50)
			16(6 ≤ T ≤ 50)
			20(8 ≤ T ≤ 50)
			24(10 ≤ T ≤ 50)
41~50 (单位1mm)	30(12 ≤ T ≤ 50)		
	3.0~5.0		
	5.5~10.0		
	10.5~20.0		
	20.5~30.0		
	30.5~40.0		
51~60 (单位1mm)	40.5~50.0		
	5.0~10.0		
	10.5~20.0		
	20.5~30.0		
	30.5~40.0		
	40.5~50.0		
61~80 (单位1mm)	5.0~10.0		
	10.5~20.0		
	20.5~30.0		
	30.5~40.0		
	40.5~50.0		
	5.0~10.0		
81~100 (单位1mm)	10.5~20.0		
	20.5~30.0		
	30.5~40.0		
	40.5~50.0		
	5.0~10.0		
	10.5~20.0		

① (D-M)/2 ≥ 2 ② T ≤ M × 8 ③ M2 · M2.6 → T ≤ M × 5



1 型号 - 2 D - 3 M - 4 T - (WCS)  
 ECTAS - D15 - M6 - T15 - WCS10

可选加工	代码	技术说明
	WCS	进行双面切割。 指定方法   WCS10 WCS = 指定单位1mm WCS ≥ M + 4 ⊗ D6~D8不可 ⊗ T尺寸选择型·T尺寸指定型不适用

