

20





型号(①代码·2D) DAJEA32

■请按步骤①~②选择型号和参数后进行订购。








 $\begin{array}{c} 6.3 \middle/ \left(\begin{array}{c} 0.4 \middle/ \end{array} \right) \end{array}$




代码	代码	D公差	材质	表面处理	硬度		
DAJEA	· 标键型	±0.2	SKS3	-	淬火硬度60~63HRC		
DAGJEA			SKS3	镀硬铬 厚度3μm以上	淬火硬度50~55HRC 镀层硬度 750HV~		
DACJEA			SUS440C	_	淬火硬度50~55HRC		
DASJEA			SUS304	_	_		
DAJJKR		g6	SUJ2	镀硬铬 厚度3~5μm	镀层硬度850HV~		
DAJKKR	- 引导型	±0.2	SKS3	_	淬火硬度60~63HRC		
DAJJSSR			SUS440C	_	淬火硬度50~55HRC		
DAJJS			SUS304	_	_		
DAJJJRL		g6	SUJ2	镀硬铬 厚度5~8μm	镀层硬度850HV~		


标准型 2-C0.8 ○ □ ±0.2 6 3.2 S T±0.05 引导型



标准型







型号		al.	4	_	S		适用	(4)	D.	
○代码	2 D	d ₁	d ₂	'	5	T	螺栓	(A)	D ₁	L
标准型 DAJEA DAGJEA DACJEA DASJEA DAJJKR	10	3.5	6.5	6	4	1	М3	2.75	_	_
	12	4.5	8	8	5	1.2	M4	3.2	8	8
	16	5.5	9.5	10	6	2	M5	5.25	8	8
	20	6.5	11	12	7	2.5	M6	7	11	10
引导型 DAJKKR DAJJSSR DAJJS DAJJJRL	25	9	14	16	9	3.5	M8	9	14	12
	32	11	17.5	20	11	5	M10	12.25	17	15
	40	14	20	24	13	7	M12	17	20	18