



1 代码 2 D — 3 公称型号 — 4 主体颜色  
**FFELL8** **FFCNC10** = **2** **1** — **W**

■ 请按步骤 ①~④ 选择型号和参数后进行订购。




型号区分: 代码 **5** 天发货

### ■ 外六角接头



**FFCNC** 螺纹部: 黄铜  
: 无电解镀镍  
**FFCNC15** 螺纹部: SUS304




材质 环部: PBT

### ■ 外螺纹弯接头



**FFELL** 螺纹部: 黄铜  
: 无电解镀镍  
**FFELL8** 螺纹部: SUS304




材质 主体: PBT

### ■ 内六角接头



**FFCNC** 螺纹部: 黄铜  
: 无电解镀镍




材质 环部: PBT

### ■ 内螺纹接头



**FFCNF** 螺纹部: 黄铜  
: 无电解镀镍




材质 环部: PBT

### ■ 隔离式接头



**FFSB** 螺纹部: 黄铜  
: 无电解镀镍



材质 环部: PBT

型号	① 代码	② D	③ 公称型号	A	内六角对边 H1	对边距离 H2	螺纹尺寸 M	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	20.1	2	8	M5×0.8	4.5	4.5	
			20.1	3	10	R1/8	3.2	8.6	
			20.1	3	14	R1/4	17.3	17.3	
			20.1	3	14	R1/4	3.2	8.6	
6	1	M5	22.6	4	11	M5×0.8	3.2	9.2	
			22.8	4	14	R1/8	11.5	18.2	
			22.8	4	17	R3/8	28.4	28.4	
			22.8	4	17	R1/8	18.7	13.7	
8	1	M5	25.7	5	13	R1/8	17.1	17.1	
			25.7	6	14	R1/4	26.9	27.3	
			25.7	6	17	R3/8	18.5	22.2	
			25.7	6	17	R1/4	26.9	27.6	
10	1	M5	27.3	8	21	R3/8	38.9	39.3	
			27.3	8	21	R1/2	28.9	48.5	
			27.3	8	21	R1/4	26.9	34.2	
			27.3	8	21	R3/8	33.5	33.5	
12	1	M5	33.8	8	21	R1/2	47.9	54.8	

型号	① 代码	② D	③ 公称型号	A	B	C	对边距离 H	螺纹尺寸 M	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	17.1	14.6	9	9	M5×0.8	3.2	4.6	
			17.1	17.8	9	10	R1/8	4.4	7.9	
			17.1	20.8	14	14	R1/4	17.3	17.3	
			17.1	20.8	14	14	R1/4	3.2	5.4	
6	1	M5	18	15.7	11.2	10	R1/8	8.5	17.8	
			18	19.9	14	14	R1/4	27.2	27.2	
			18	21.9	17	17	R3/8	10.4	10.4	
			18	22.9	17	17	R3/8	15	19.1	
8	1	M5	23.6	20.3	13.6	14	R1/4	15	19.1	
			23.6	22.8	13.6	14	R1/4	28.4	28.4	
			23.6	23.8	17	17	R3/8	22.1	20.8	
			23.6	23.8	17	17	R3/8	25.5	25.5	
10	1	M5	25	23.6	16.3	17	R3/8	31.5	27.5	
			25	26.1	16.3	17	R3/8	47.2	47.2	
			25	29.1	21	21	R1/2	41.7	31.1	
			25	29.1	21	21	R1/2	33.1	33.1	
12	1	M5	32.2	28	19.7	17	R3/8	42.8	33.1	
			32.2	31	19.7	17	R1/2	52.8	52.8	

型号	① 代码	② D	③ 公称型号	A	对边距离 H2	螺纹尺寸 M	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	21.5	10	M5×0.8	4	6	
			20.5	10	R1/8	4	8	
			19.5	14	R1/4	4.4	9	
			23	12	M5×0.8	10.3	11	
6	1	M5	23.5	14	R1/4	10.3	18	
			21.5	17	R3/8	26	26	
			21.5	17	R1/8	17.5	18	
			21.5	17	R1/8	22.4	17	
8	1	M5	27	14	R1/4	17.5	26	
			27	14	R1/4	22.4	24	
			27	14	R1/8	17.5	26	
			27	14	R1/8	22.4	24	
10	1	M5	31	17	R1/8	17.5	26	
			32.5	17	R1/4	22	22	
			28.5	17	R3/8	30.5	26	
			28.5	17	R3/8	49	49	
12	1	M5	26.5	22	R1/2	37	37	
			35.5	19	R1/4	32	32	
			30.5	19	R3/8	40	40	
			29.5	22	R1/2	45	51	

型号	① 代码	② D	③ 公称型号	A	B	C	对边距离 H	螺纹尺寸 M	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	18	15	8	8	M5×0.8	3.2	5	
			18.5	20.5	10	10	R1/8	3.5	8	
			24	14	14	14	R1/4	15	15	
			20	15	10	M5×0.8	4.2	7		
6	1	M5	24	12.5	12	12	R1/8	8	13	
			21	27.5	14	R1/4	8	18		
			29	17	R3/8	17	26			
			25.5	17	R1/8	17	17			
8	1	M5	23.5	28.5	14.5	14	R1/4	18	20	
			30	17	R3/8	18	28			
			28	17.5	R1/8	24.3	26			
			31	17	R1/4	28	28			
10	1	M5	32.5	17.5	17	R3/8	27	33		
			35.5	22	R1/2	49	49			
			33	19	R1/4	37	37			
			29.5	34.5	20	22	R3/8	35	43	

型号	① 代码	② D	③ 公称型号	A	内六角对边 H	φd	螺纹尺寸 M	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	20.1	2	8.2	M5×0.8	3.2	4.2	
			20.1	3	10	R1/8	8	8	
			21.8	2	11	M5×0.8	7.2	7.2	
			22	4	11	R1/8	8.6	8.6	
6	1	M5	22.8	4	13.5	R1/4	11.5	16.8	
			22.8	4	13.5	R1/8	18.7	13.1	
			23.7	6	17	R3/8	15.5	15.5	
			23.7	6	17	R3/8	26.9	25.9	
8	1	M5	29.4	5	15.5	R1/8	18.5	18	
			32.4	6	15.5	R1/4	26.9	23.3	
			28.4	8	17	R3/8	25.7	25.7	
			27.3	8	21	R1/2	38.9	46.7	
10	1	M5	35.4	6	18.8	R1/4	26.9	29.7	
			31.8	8	18.8	R3/8	30.2	30.2	
			33.8	8	21	R1/2	47.9	50.6	

型号	① 代码	② D	③ 公称型号	A	B	对边距离 H	螺纹尺寸 Rc	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	24.4	11	13	Rc1/8	3.2	13.5	
			27.4	14	17	Rc1/4	24.9	24.9	
			25.4	11	13	Rc1/8	14.8	14.8	
			28.4	14	17	Rc1/4	26.1	26.1	
6	1	M5	29.4	15	19	Rc3/8	27.6	27.6	
			27.7	10	13	Rc1/8	16.4	16.4	
			30.7	14	17	Rc1/4	27.7	27.7	
			31.7	15	19	Rc3/8	29.2	29.2	
8	1	M5	32.4	13	17	Rc1/4	30.3	30.3	
			33.4	15	19	Rc3/8	32.5	32.5	
			36.4	18	24	Rc1/2	53.6	53.6	
			35.4	12	19	Rc1/4	45.3	45.3	
12	1	M5	36.4	15	19	Rc3/8	39.4	39.4	
			39.4	18	24	Rc1/2	60.6	60.6	

型号	① 代码	② D	③ 公称型号	A	B	对边距离 H1	对边距离 H2	螺纹尺寸 M×螺距	螺纹尺寸 Rc	有效截面积 (mm <sup>2</sup> )	重量 (g)
4	1	M5	25.1	11	14	14	M12×1.0	Rc1/8	3.2	18	
			26.3	9	17	17	M14×1.0	Rc1/8	11	26	
			31.3	14	17	17	M14×1.0	Rc1/4	30	30	
			28.9	8	19	19	M16×1.0	Rc1/8	25.2	34.5	
6	1	M5	34.9	14	19	19	M16×1.0	Rc1/4	42.5	42.5	
			35.9	15	19	19	M16×1.0	Rc3/8	36	36	
			32.3	13	24	22	M20×1.0	Rc1/4	38.7	58.5	
			34.3	15	24	22	M20×1.0	Rc3/8	55	55	
12	1	M5	37.4	14	26	24	M22×1.0	Rc3/8	71.5	71.5	
			41.4	18	26	24	M22×1.0	Rc1/2	44.6	70.5	

橡皮管/快速接头/吸盘及配件

