



联轴器

膜片式联轴器

免键型 (单膜片型/双膜片型)



型号(①代码·②NO) — ③d1 — ④d2
 CADH80 — 22 — 25
 CADHP90L — 24 — 28



■ 请按步骤①~④选择型号和参数后进行订购。



型号区分: 7 天发货



CADH (单膜片型)





代码	主体		膜片	附件
	材质	表面处理		
CADH	S45C	发黑	不锈钢	锁紧螺栓 止动螺丝

① 代码	② No.	③ d1、④ d2 选择 (但d1≤d2)																D	L	L1	W	M	M1	M2					
CADH	56	14	16	18	19	20	22	24											56	65	29	7.0	M 5	4-M5	2-M5				
	70							24	25	28	30	32	35						70	65	29	7.0	M 6	4-M6	2-M6				
	70L				18	19	20	22	24	25	28	30	32	35					70	90	41.5	7.0	M 6	4-M6	2-M6				
	80				18	19	20	22	24	25	28	30	32	35					80	70	31	8.0	M 8	4-M6	2-M6				
	80L				18	19	20	22	24	25	28	30	32	35					80	95	43.5	8.0	M 8	4-M6	2-M6				
	90									28	30	32	35	38	40	42	45	48	90	91	70	8.0	M 8	6-M6	3-M6				
	90L									28	30	32	35	38	40	42	45	48	90	110	50.5	9.0	M 8	6-M6	3-M6				
	100										32	35	38	40	42	45	48	50	52	55	60	100	70	31	8.0	M 8	6-M6	3-M6	
	100L										32	35	38	40	42	45	48	50	52	55	60	100	124	57.0	10.0	M 8	6-M6	3-M6	
	126											38	40	42	45	48	50	52	55	60	62	65	126	100	44.5	11.0	M10	6-M6	3-M6
	126L											38	40	42	45	48	50	52	55	60	62	65	126	152	70.5	11.0	M10	6-M6	3-M6
	144																		144	118	53	12.0	M12	6-M8	3-M8				
	144L																		144	170	79.0	12.0	M12	6-M8	3-M8				

① 代码	② No.	额定扭矩 (N·m)	最大扭矩 (N·m)	最高转速 (rpm)	惯性力矩 (kg·m ²)	静态扭矩刚性 (N·m/rad)	径向偏差 (mm)	角向偏差 (°)	轴向偏差 (mm)	重量 (g)
CADH	56	50	100	18000	0.42 × 10 ⁻³	41 × 10 ³	0.02	0.5	± 0.5	680
	70	70	140	17000	0.65 × 10 ⁻³	58 × 10 ³				904
	70L	70	140	17000	0.75 × 10 ⁻³	67 × 10 ³				1250
	80	125	250	16000	1.0 × 10 ⁻³	62 × 10 ³				1178
	80L	125	250	16000	1.15 × 10 ⁻³	71 × 10 ³				1550
	90	180	360	14000	2.0 × 10 ⁻³	140 × 10 ³				1943
	90L	180	360	14000	2.3 × 10 ⁻³	160 × 10 ³				2100
	100	280	560	12000	2.95 × 10 ⁻³	160 × 10 ³				1946.5
	100L	280	560	12000	3.39 × 10 ⁻³	184 × 10 ³				2250
	126	450	900	10000	6.35 × 10 ⁻³	450 × 10 ³				4042
	126L	450	900	10000	7.3 × 10 ⁻³	517 × 10 ³				4500
	144	760	1520	8000	11.33 × 10 ⁻³	785 × 10 ³				4502
	144L	760	1520	8000	13 × 10 ⁻³	902 × 10 ³				8039



CADHP (双膜片型)



代码	主体		膜片	附件
	材质	表面处理		
CADHP	S45C	发黑	不锈钢	锁紧螺栓 止动螺丝

① 代码	② No.	③ d1、④ d2 选择 (但d1≤d2)																			D	L	L1	L2	W	M	M1	M2					
CADHP	56	14	16	18	19	20	22	24															56	80	29	8	7.0	M 5	4-M5	2-M5			
	70			18	19	20	22	24	25	28	30	32	35										70	80	29	8	7.0	M 6	4-M6	2-M6			
	70L			18	19	20	22	24	25	28	30	32	35									70	105	41.5	8	7.0	M 6	4-M6	2-M6				
	80			18	19	20	22	24	25	28	30	32	35									80	88	31	10	8.0	M 8	4-M6	2-M6				
	80L			18	19	20	22	24	25	28	30	32	35									80	113	43.5	10	8.0	M 8	4-M6	2-M6				
	90				20	22	24	25	28	30	32	35		38	40	42	45	48					90	88	31	10	8.0	M 8	6-M6	3-M6			
	90L				20	22	24	25	28	30	32	35		38	40	42	45	48					90	129	50.5	10	9.0	M 8	6-M6	3-M6			
	100					24	25	28	30	32	35	38	40	42	45	48		50	52	55	60		100	88	31	10	8.0	M 8	6-M6	3-M6			
	100L					24	25	28	30	32	35	38	40	42	45	48		50	52	55	60		100	144	57.0	10	10.0	M 8	6-M6	3-M6			
	126						28	30	32	35	38	40	42	45	48		50	52	55	60	62	65	126	125	44.5	14	11.0	M10	6-M6	3-M6			
	126L						28	30	32	35	38	40	42	45	48		50	52	55	60	62	65	126	177	70.5	14	11.0	M10	6-M6	3-M6			
	144										32	35	38	40	42	45	48	50	52	55	60	62	65	70	75	144	144	53	14	12.0	M12	6-M8	3-M8
	144L										32	35	38	40	42	45	48	50	52	55	60	62	65	70	75	144	196	79.0	14	12.0	M12	6-M8	3-M8

① 代码	② No.	额定扭矩 (N·m)	最大扭矩 (N·m)	最高转速 (rpm)	惯性力矩 (kg·m ²)	静态扭矩刚性 (N·m/rad)	径向偏差 (mm)	角向偏差 (°)	轴向偏差 (mm)	重量 (g)
CADHP	56	50	100	15000	0.61×10 ⁻³	22 × 10 ³	0.02	1	± 1.0	780
	70	70	140	13000	0.81×10 ⁻³	30 × 10 ³				2902.5
	70L	70	140	13000	0.93×10 ⁻³	34 × 10 ³				1580.5
	80	125	250	11000	1.32×10 ⁻³	32 × 10 ³	0.03			1503.5
	80L	125	250	11000	1.52×10 ⁻³	37 × 10 ³				1730
	90	180	360	10000	2.56×10 ⁻³	68 × 10 ³				2408.5
	90L	180	360	10000	2.95×10 ⁻³	78 × 10 ³				2300
	100	280	560	8000	3.68×10 ⁻³	79 × 10 ³				2471.5
	100L	280	560	8000	4.23×10 ⁻³	91 × 10 ³				2550
	126	450	900	10000	7.95×10 ⁻³	216 × 10 ³				5238
	126L	450	900	7000	9.14×10 ⁻³	248 × 10 ³	5835			
	144	760	1520	8000	16.7×10 ⁻³	380 × 10 ³	6080.5			
	144L	760	1520	6500	19.2×10 ⁻³	437 × 10 ³	9420			

询价④种方式



官网 <http://www.srdfaa.com>
 深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
 客服热线 0755-27926613