



代码	类型	材质	表面处理	安装使用示例		选型示例： HA41-BL-5010-Y-50100 (单品) HA41-BL-5010-Y-50100-T	
HA31-BL-5010 HA41-BL-5010	钣金连接件	SPCC SUS304	镀锌 单面拉丝			HA31-BL-5010-Y-50100-T (欧标型材配用)	HA41-BL-5010-Y-50100-T (欧标型材配用)
						 X1挤压角码	 X1挤压角码
						 X4 M8X16螺栓	 X4 M8X16螺栓
						 X4 M8平垫圈	 X4 M8平垫圈
						 X4 M8弹簧垫圈	 X4 M8弹簧垫圈
						 X4 M8 T型螺母	 X4 M8 T型螺母

槽口	型号	材质	表面处理	重量(g)	用途
	HA31-BL-5010-Y-50100 (单品供货)	SPCC	镀锌	412	用于两根槽宽为10.2mm的欧标型材水平延长连接，配用8颗M8的螺栓及相对应的T型螺母，弹簧垫圈和平垫圈。
	HA31-BL-5010-Y-50100-T(成套供货)			628	
	HA41-BL-5010-Y-50100 (单品供货)	SUS304	单面拉丝	412	
	HA41-BL-5010-Y-50100-T(成套供货)			628	

代码	类型	材质	表面处理
HA31-BL-5010	钣金连接件	SPCC	镀锌
HA41-BL-5010		SUS304	单面拉丝

Technical drawing of the HA31-BL-5010-X-5050-T connector. The drawing shows a cross-section of the connector with dimensions: 200 (total width), 180 (inner width), 80 (flange width), 48 (flange thickness), 100 (height), 3 (hole offset), and Ø8.50 (hole diameter). A detail view shows a hole with a 3mm offset.

安装使用示例

3D assembly diagram showing the HA31-BL-5010-X-5050-T connector being installed between two profiles. The diagram shows the connector being placed over the profiles and then secured with bolts and nuts.

选型示例:

HA41-BL-5010-X-5050 (单品)

HA41-BL-5010-X-5050-T

HA31-BL-5010-X-5050-T (欧标型材配用)	HA41-BL-5010-X-5050-T (欧标型材配用)
 X1 钣金连接件	 X1 钣金连接件
 X6 M8X16螺栓	 X6 M8X16螺栓
 X6 M8平垫圈	 X6 M8平垫圈
 X6 M8弹簧垫圈	 X6 M8弹簧垫圈
 X6 M8 T型螺母	 X6 M8 T型螺母

槽口	型号	材质	表面处理	重量(g)	用途
	HA31-BL-5010-X-5050 (单品供货)	SPCC	镀锌	282	用于两根槽宽为10.2mm的欧标型材水平延长连接, 配用6颗M8的螺栓及相对应的T型螺母, 弹簧垫圈和平垫圈。
	HA31-BL-5010-X-5050-T(成套供货)			444	
	HA41-BL-5010-X-5050 (单品供货)	SUS304	单面拉丝	282	
	HA41-BL-5010-X-5050-T(成套供货)			444	

代码	类型	材质	表面处理	安装使用示例		选型示例： HA41-BL-5010-X-50100 (单品) HA41-BL-5010-X-50100-T	
HA31-BL-5010 HA41-BL-5010	钣金连接件	SPCC SUS304	镀锌 单面拉丝				

