








代码	类型	材质	表面处理	安装使用示例	
HA01-JY-408	挤压角码	6063-T5	喷砂氧化		
				HA01-JY-408-70-110 (单品) HA01-JY-408-70-110-GT HA01-JY-408-70-110-GT (国标型材配用)	
槽口	型号	材质	表面处理	重量(g)	用途
	HA01-JY-408-70-110 (单品供货)	6063-T5	喷砂氧化	392.7	用于两根槽宽为8.2mm的国标型材135度角连接, 配用6颗M6的螺栓及相对应的T型螺母, 弹簧垫圈和平垫圈。
	HA01-JY-408-70-110-GT(成套供货)			477	

代码	类型	材质	表面处理	安装使用示例		选型示例： HA41-BL-408-Y-4040 (单品) HA41-BL-408-Y-4040-GT	
HA31-BL-408	钣金连接件	SPCC	镀锌			HA31-BL-408-Y-4040-GT (国标型材配用)	HA41-BL-408-Y-4040-GT (国标型材配用)
HA41-BL-408		SUS304	单面拉丝				
槽口	型号	材质	表面处理	重量(g)	用途		
	HA31-BL-408-Y-4040 (单品供货)	SPCC	镀锌	53	用于两根槽宽为8.2mm的国标型材水平延长连接, 配用2颗M6的螺栓及相对应的T型螺母, 弹簧垫圈和平垫圈。		
	HA31-BL-408-Y-4040-GT(成套供货)			77.5			
	HA41-BL-408-Y-4040 (单品供货)	SUS304	单面拉丝	53			
	HA41-BL-408-Y-4040-GT(成套供货)			77			

代码	类型	材质	表面处理	安装使用示例		选型示例： HA41-BL-408-Y-4080 (单品) HA41-BL-408-Y-4080-GT	
HA31-BL-408 HA41-BL-408	钣金连接件	SPCC SUS304	镀锌 单面拉丝			HA31-BL-408-Y-4080-GT (国标型材配用)	HA41-BL-408-Y-4080-GT (国标型材配用)
							
槽口	型号	材质	表面处理	重量(g)	用途		
	HA31-BL-408-Y-4080 (单品供货)	SPCC	镀锌	256	用于两根槽宽为8.2mm的国标型材水平延长连接, 配用8颗M6的螺栓及相对应的T型螺母, 弹簧垫圈和平垫圈。		
	HA31-BL-408-Y-4080-GT(成套供货)			352.6			
	HA41-BL-408-Y-4080 (单品供货)	SUS304	单面拉丝	256			
	HA41-BL-408-Y-4080-GT(成套供货)			352			

