



型号(①代码·②d)
ADHBL20

■ 请按步骤①~②选择型号和参数后进行订购。





型号区分:
代码 **7** 天发货





① 代码			内置直线轴承	固定座		使用环境温度
双衬型	中长型	加长型	ADMU	材质	表面处理	-20~80℃
ADHBL	ADHBS	ADHLL		铝合金	本色阳极氧化处理	

■ 特点: 安装方便, 大幅缩短组装机时。



双衬型



中长型



加长型



滚珠
导向轴
组件
04

②d	公差			L			L ₁			h	H	(H ₁)	(H ₂)	W	W ₁	W ₂	M	d ₁	ℓ	(A)	(B)	N	P
	双衬型	中长型	加长型	双衬型	中长型	加长型	双衬型	中长型	加长型														
5	0	-0.008	-	33	-	25	-	-	7	14	11	-	22	16	3	M3	-	-	-	-	-	-	-
6	0	-	-	48	-	36	-	-	9	18	15	-	30	20	5	M4	3.4	8	12	-	-	-	-
8	0	-	-	58	-	42	-	-	11	22	18	6	34	24	5	M4	3.4	8	16	0.4	7.5	-	-
10	0	-	-	68	-	93	46	-	70	13	26	21	40	28	6	M5	4.3	12	15.5	-	-	-	-
12	-0.010	-	0	70	-	96	-	-	72	15	28	24	42	30.5	5.75	M5	4.3	12	17.5	-	7	7	-
13	-0.010	-	-0.015	75	-	103	50	-	78	15	30	24.5	44	33	5.5	M5	4.3	12	19	0.85	6.5	-	-
16	-0.015	-	-	85	100	118	60	74	88	19	38.5	32.5	9	50	36	M6	5.2	18	19.8	-	6.5	-	-
20	0	0	0	96	115	134	70	84	100	21	41	35	11	54	40	M6	5.2	18	21	0.5	7.5	8	-
25	-0.012	-0.018	-0.018	130	160	185	100	118	138	26	51.5	42	12	76	54	M8	7	18	36	1	4.5	9	-
30	-0.012	-0.018	-0.018	140	170	200	110	130	150	30	59.5	49	15	78	58	M8	7	18	39.9	0.75	5.5	-	-
35	-0.015	-	-	155	-	-	120	-	34	68	54	18	90	70	10	M10	8.7	25	53	-	6	-	-
40	-0.015	-	-	175	-	-	140	-	40	78	62	20	102	80	11	M10	8.7	25	61	1.5	5.5	-	-
50	-0.015	-	-	215	-	-	160	-	52	102	80	25	122	100	11	M10	8.7	25	81	-	5.5	-	-

②d	基本额定负载						静态容许力矩			重量(g)		
	C(动) N			Co(静)N			N·m			g		
	双衬型	中长型	加长型	双衬型	中长型	加长型	双衬型	中长型	加长型	双衬型	中长型	加长型
5	263	-	-	412	-	-	1.38	-	-	27	-	-
6	324	-	-	529	-	-	2.18	-	8.2	63	-	-
8	431	-	-	784	-	-	4.31	-	16.0	102	-	-
10	588	-	588	1100	-	1100	7.24	-	27.0	180	-	241
12	657	-	657	1200	-	1200	10.9	12.0	40.1	205	-	289
13	813	-	813	1570	-	1570	11.6	-	42.9	240	-	324
16	1230	1230	1230	2350	2350	2350	19.7	25.5	73.5	400	447	527
20	1400	1400	1400	2740	2740	2740	26.8	35.0	98.0	570	588	682
25	1560	1560	1560	3140	3140	3140	43.4	63.1	157	1200	1397	1586
30	2490	2490	2490	5490	5490	5490	82.8	106	297	1480	1693	1960
35	2650	-	-	6270	-	-	110	-	373	2200	-	-
40	3430	-	-	8040	-	-	147	-	553	3200	-	-
50	6080	-	-	15900	-	-	397	-	-	6700	-	-

国际单位 1N=0.102kgf

