



型号(1代码·2规格)
FBC012

■请按步骤①~②选择型号和参数后进行订购。





型号区分:
代码 5 天发货

■ LBH型



代码	类型	材质	硬度 (肖氏)	颜色	使用 温度范围	用途
FBCO	LBH型	丁腈橡胶	HS85±5	黑色	-20~100℃	往复运动的轴用 防刮油的防尘密封

■安装图例



型号		d	D	C	h	d ₁	D ₁	H	S	B
① 代码	② 规格									
FBCO	12	12	20	6	4.5	10.8	20	5	16.3	2
	12.5	12.5	20.5			11.3	20.5		16.8	
	14	14	22			12.8	22		18.3	
	18	18	26			16.8	26		22.3	
	20	20	28			18.8	28		24.3	
	22	22	30			20.8	30		26.3	
	22.4	22.4	30.4			21.2	30.4		26.7	
	28	28	36			26.5	36		32.3	
	30	30	38			28.5	38		34	
	31.5	31.5	39.5	6.5	5	30	39.5	6	35.5	
	32	32	40			30.5	40		36	
	35	35	43			33.5	43		39	
	35.5	35.5	43.5			34	43.5		39.5	
	36	36	44			34.5	44		40	
	38	38	46			36.5	46		42	
	40	40	48			38.5	48		44	
	45	45	53			43.5	53		49	
	50	50	58			48.5	58		54	
	53	53	61			51.2	61		57	
	55	55	63			53.2	63		59	
	56	56	64			54.2	64		60	
	60	60	68			58.2	68		64	
	63	63	71			61.2	71		67	
	65	65	73			63.2	73		69	
	67	67	75			65.2	75		71	
	70	70	80	8	6	68.2	80	7	75	3
	71	71	81			69.2	81		76	
	75	75	85			73.2	85		80	
	80	80	90			78.2	90		85	
	85	85	95			83.2	95		90	
	90	90	100			88.2	100		95	
	95	95	105			93.2	105		100	
	100	100	110			97.8	110		105	



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达