

# 圆皮带用滑轮 ▶ 平皮带/圆皮带/滑轮/惰轮

## 双联型




型号 (1) 代码 · (2) P.D.) - (3) R - (4) P  
CDWAC30 - 1.6 - P5

■ 请按步骤 ①~④ 选择型号和参数后进行订购。




型号区分: 代码 7 天发货

■ 圆皮带用滑轮



代码	材质	表面处理	附件
CDWAC	铝合金	本色阳极氧化处理	2个止动螺丝 (SCM435四氧化三铁保护膜)

6.3 / (1.6)




① 轴承采用压入方式。不可以拆卸。

型号		③ R	④ 轴孔规格 P(H7) 最小单位1mm	S	D	D <sub>1</sub>	D <sub>2</sub>	L	l	B	M (粗牙螺纹)	附件 止动螺丝	适用 圆皮带直径	
① 代码	② P.D.													
CDWAC	15	1.1	3~8	4	12	17	13	14	3	5.8	M3	M3×3	2	
	20		4~10		16	22	18							
	30		4~12		20	32	28							
	20	1.6	3~10	5	16	22	17	16	3	5.8	M3	M3×3	3	
	30		5~12		20	32	27							
	40		5~20		30	42	37							
	45				30	47	42							
	23	2.1	5~12	6	20	25	19	18	3	5.8	M3	M3×3	4	
	28				30	32	26							
	30				42	36								
	40				25	47	41							
	45		30		50	44								
	48	5~18	20	42	35	22	4	7.8	M4	M4×3	5			
	28	5~12	20	30	23	20	3	5.8	M3	M3×3				
	40	2.6	5~20	7	30	42	35	22	4	7.8	M4	M4×3		
	50				52	45								
	28	3.1	5~12	8	30	22	30	22	22	3	5.8	M3	M3×3	6
	38					40	32							
	48					50	42							
	50					52	44							
60	62					54								
75	77					69								
100	102	94												
50	4.1	5~20	10	30	52	42	30	5	9.8	M5	M5×4	8		
60					62	52								
100					102	92								
60	5.1	5~20	12	34	62	50	34	5	9.8	M5	M5×4	10		
100					102	90								
140					142	130								



型号 (1) 代码 · (2) P.D.) - (3) R - (4) P - (DC)  
CDWAC40 - 2.6 - P8 - DC

可选加工	外径切割											
代码	DC											
技术说明	<p>切割D<sub>1</sub>尺寸, 减小外径。 指定方法 DC</p> 	<table border="1"> <thead> <tr> <th>适用R</th> <th>DC</th> </tr> </thead> <tbody> <tr> <td>1.1</td> <td>P.D. + 0.8</td> </tr> <tr> <td>1.6</td> <td>P.D. + 1.2</td> </tr> <tr> <td>2.1</td> <td>P.D. + 1.6</td> </tr> <tr> <td>2.6</td> <td>P.D. + 1.8</td> </tr> </tbody> </table> <p>① 仅适用于皮带直径1.1、1.6、2.1、2.6的产品 ② 外径切割的加工面可能不进行表面处理。</p>	适用R	DC	1.1	P.D. + 0.8	1.6	P.D. + 1.2	2.1	P.D. + 1.6	2.6	P.D. + 1.8
适用R	DC											
1.1	P.D. + 0.8											
1.6	P.D. + 1.2											
2.1	P.D. + 1.6											
2.6	P.D. + 1.8											

平皮带  
圆皮带  
惰轮



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

**SRD 仕瑞达**