



## 平皮带/圆皮带/滑轮/惰轮

## 圆皮带用惰轮

## 双联型



型号 (1) 代码 · (2) P.D.)

CDXAC30

(3) R

- 1.6

■ 请按步骤①~③选择型号和参数后进行订购。



型号区分:

代码


7 天发货

## 圆皮带用惰轮



代码	材质		表面处理	附件
	轴承	主体		
CDXAC	钢	铝合金	本色阳极氧化处理	扣环 (SUS304)

6.3 (1.6/)



\*轴承精度JIS B1514 0级  
①轴承采用压入方式。不可以拆卸。

型号		③ R	S	d	P	dh	D	D <sub>1</sub>	T	B	C	使用轴承	适用圆皮带直径			
① 代码	② P.D.															
CDXAC	15	1.1	4	3	10	8	17	13	9	4	2.5	623ZZ	2			
	20			4	13	11	22	18	10	5		624ZZ				
	30			6	19	16	32	28	11	6		626ZZ				
	20	1.6	5	4	13	11	22	17	11	5	3	624ZZ	3			
	30			6	19	16	32	27		6	2.5	626ZZ				
	40			10	26	23	42	37	14	8	3	6000ZZ				
	45						47	42								
	23					15	13	25		19	5	4		696ZZ		
	28	2.1	6	6	6	19	16	30	24	13	6	3.5	626ZZ	4		
	30							32	26							
	40							42	36							
	45							47	41							
	48				10	26	23	50	44	14	8	3	6000ZZ			
	28	2.6	7	7	8	19	16	30	23	15	6	4.5	698ZZ	5		
	40				10	26	23	42	35		8	4	6000ZZ			
	50				12	32	27	52	45		10	3	6201ZZ			
	28				6	19	16	30	22		17	6	5.5		626ZZ	
	38	3.1	8	8	10	26	23	40	32	18	8	5	6000ZZ	6		
	48							50	42							
	50							52	44							
	60							62	54							
	75				12	32	27	77	69		10	4	6201ZZ			
	100				102	94										
	50	4.1	10	10	12	32	27	52	42	21	10	5.5	6201ZZ	8		
60	62				52											
100	15				35	30	102	92	11		5	6202ZZ				
60	5.1	12	12	15	35	30	62	50	25	11	7	6202ZZ	10			
100							102	90								
140							142	130								



型号 (1) 代码 · (2) P.D.) - (3) R - (DC)

CDXAC40 - 2.6 - DC

可选加工


外径切割

代码

DC

技术说明

切割D<sub>1</sub>尺寸，减小外径。  
指定方法 DC



适用R	DC
1.1	P.D. + 0.8
1.6	P.D. + 1.2
2.1	P.D. + 1.6
2.6	P.D. + 1.8

①仅适用于皮带直径1.1 · 1.6 · 2.1 · 2.6的产品  
②外径切割的加工面可能不进行表面处理。

