



① 代码 — ② D1-D2/No./D
FFCRS — 4-4
FFPJ8

■ 请按步骤①~②选择型号和参数后进行订购。




型号区分: 5 天发货

■ 四通接头



FFCRS

材质: PBT




■ L型长插头



FFLCN

材质: PBT




■ 异径插头



FFRDS

材质: PBT




■ 连接插头



FFPJ

材质: PBT



型号		C1	C2	φd	E1	E2	F	φG	重量 (g)
① 代码	② D1-D2								
FFCRS	4-4	14.6	14.6	3.2	17.4	17.4	7.3	10.5	8.5
	6-4	17.1	14.6	3.2	20.7	20.7	8.1	12.4	11.5
	6-6	17.1	17.1	3.2	20.7	20.7	8.1	12.4	12.5
	8-6	18.9	17.6	3.2	23.6	23.4	9.2	14.3	18
	8-8	18.9	18.9	3.2	23.6	23.6	9.2	14.3	16
	10-8	20.3	18.9	4.2	26	26	11.3	17.8	32
	10-10	20.3	20.3	4.2	26	26	11.3	17.8	30
	12-10	28.2	20.3	4.2	29.7	29.7	13	22.3	47
	12-12	28.2	28.2	4.2	29.7	29.7	13	22.3	45

型号		管径 D1	管径 D2	B	C1	C2	E	G	L	重量 (g)
① 代码	② No.									
FFLCN	4-4	4	4	25.5	14.4	15.3	16.8	10.5	15.5	2.5
	6-4				15.6	17.2	19.6	12.4	17.5	3.5
	6-6	6	6	28.5	16.5	18.2	21.6	14.3	19.9	4
	8-6				16.5					5
	8-8	8	8	30.9	17.8	20.4	21.8	17.8	22.3	5.5
	10-8				17.8					12
	10-10	10	10	33.8	19.2	20.4	24.2	17.8	22.3	13
	12-10				19.7	24.7	28.3	21.2	26.3	14
	12-12	12	12	40.3	21.9					14.5

型号		管径 D1	管径 D2	B	C1	C2	G	L	重量 (g)
① 代码	② No.								
FFRDS	6-4	6	4	41.5	17	14.4	10.5	24.5	3
	8-4								
	8-6	8	6	45	18	16.5	12.4	27	4
	10-6								
	10-8	10	8	46.8	20	17.8	14.3	27	6
	12-8								
	12-10	12	10	54	23.5	19.2	17.8	30.5	7

型号		B	C	P	重量 (g)
① 代码	② 管径D(φ)				
FFPJ	4	34.2	14.7	5.3	0.2
	6	39.3	16.5	7.2	0.9
	8	42.6	18	9.2	1.4
	10	45	19.4	11.3	2.0
	12	51.6	22.4	13.3	2.5

规格	
使用流体	压缩空气
使用压力范围	0~0.9MPa
保证耐压力	1.0MPa
保证真空压力	-100kPa
使用温度范围	5~60℃



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达