



1 代码 2 D — 3 公称型号  
FFCPTK6 — 2


■ 请按步骤 1~3 选择型号和参数后进行订购。



型号区分: 4 天发货

■ 直立压合接头

FFCPTK  
FFCPTY



材质 SUS316


型号		3 公称型号	T R/PT	适用气管内径 (mm)	L	l	对边间距	
1 代码	2 适用气管外径 (mm)						B1	B2
FFCPTK	4	1	1/8	2	24	9	10	10
		2	1/4		26	11	14	
	6	1	1/8	4	28.5	11	14	12
		2	1/4		30	12	17	
	8	1	1/8	6	28	9	14	14
		2	1/4		30	11	14	
10	3	3/8	8	31	12	17	17	
	4	1/2		32	11	17		
12	2	1/4	10	34	11	17	19	
	3	3/8		35	12	17		
	4	1/2		38	15	22		

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L	l	对边间距	
1 代码	2 适用气管外径 (mm)						B1	B2
FFCPTY	4	1	1/8	2.5	24	9	10	10
		2	1/4		26	11	14	
	8	1	1/8	5	28	9	14	14
		2	1/4		30	11	14	
	10	3	3/8	6.5	31	12	17	17
		4	1/2		32	11	17	
12	2	1/4	8	33	12	17	19	
	3	3/8		36	15	22		
	4	1/2		38	15	22		

① FFCPTK与FFCPTY的区别在于适用气管的内径。请根据使用的气管进行选择。

■ 弯压合接头

FFCLPTK  
FFCUNE



材质 SUS316

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L1	L2	l	对边间距	
1 代码	2 适用气管外径 (mm)							B1	B2
FFCLPTK	4	1	1/8	2	18	20	9	12	10
		2	1/4		21	21	11	14	
	6	1	1/8	4	18	21.5	9	12	12
		2	1/4		21	22.5	11	14	
	8	3	3/8	6	23	23.5	12	17	14
		4	1/2		19	24	9	14	
10	2	1/4	8	21	24	11	14	14	
	3	3/8		23	26.5	12	17		
12	4	1/2	10	29	28.5	15	22	17	
	2	1/4		23	27.5	11	17		
	3	3/8		27	30	12	22	19	
	4	1/2		30	30	15	22		

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L1	L2	l	对边间距	
1 代码	2 适用气管外径 (mm)							B1	B2
FFCUNE	4	1	1/8	2.5	18	20	9	12	10
		2	1/4		21	21	11	14	
	8	1	1/8	5	19	24	9	14	14
		2	1/4		21	24	11	14	
	10	3	3/8	6.5	23	25	12	17	17
		4	1/2		22	26.5	11	17	
12	2	1/4	8	23	26.5	12	17	17	
	3	3/8		29	28.5	15	22		
	4	1/2		27	30	12	22	19	
				30	30	15	22		

