20



■请按步骤①~⑦选择型号和参数后进行订购。

DAKSTAGS10 - P8.00 - L15 - B8.0 - E3.0 - A30

小头锥角型 ▶









代	码	材质	表面处理	硬度淬火硬度60~63HRC淬火硬度50~55HRC镀层硬度 750HV~		
圆型	多棱型	例如	衣山火埕			
DAKSTA	DAKSTD	9CrWMn(SKS3)	_			
DAGKSTA	DAGKSTD	9CrWMn(SKS3)	镀硬铬 厚度3μm以上			
DACKSTA	_	9Cr18(SUS440C)	_	淬火硬度50~55HRC		
DASKSTA	DASKSTD	SUS304	_	_		
	DABQSSR	9Cr18(SUS440C)	_	淬火硬度48~53HRC		

●内螺纹型





■公差选择

D	❷ · ❸D · P公差									
或 P	M P		G	H	S					
Р	m6	p6	g6	h7	_					
3.00	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	0 -0.010						
3.01~ 6.00	+0.012 +0.004	+0.020 +0.012	-0.004 -0.012	0 -0.012						
6.01~10.00	+0.015 +0.006	+0.024 +0.015	-0.005 -0.014	0 -0.015	0 -0.01					
10.01~18.00	+0.018 +0.007	+0.029 +0.018	-0.006 -0.017	0 -0.018						
18.01~20.00	+0.021 +0.008	+0.035 +0.022	-0.007 -0.020	0 -0.021						

■内螺纹底孔表

螺纹直径 M2 M3 M4 M5 M8 底孔直径d2 1.8 2.6 3.4 4.3 6.9						
底孔直径d2 1.8 2.6 3.4 4.3 6.9	螺纹直径	M2	M3	M4	M5	M8
	底孔直径d2	1.8	2.6	3.4	4.3	6.9
底孔深度U 8 9.5 12 14.5 21	底孔深度U	8	9.5	12	14.5	21











型 号					6 P	6L		0.5	® E	0.00					
○ 代 码		②D尺寸公差 ③P尺寸公差		○D 最小单位	最小单位	最小单位1mm		7 B 最小单位0.1mm	最小单位	^⑨ A° 选择	D	M (粗牙螺纹)	l	(W)	
		选择	选择	00	0.01mm	圆型	多棱型	取小平位0.111111	0.1mm	251年		(和2/1 孫以)			
				5	3.00~ 5.00	8~10	8~10	2.0~15.0(10.0)			5	M2	3	1.2	
<圆型> <多棱型> DAKSTA DAKSTD	<多棱型>			6	4.00~ 6.00	8~17	9~17	2.0~15.0			6	M3	5	1.5	
				8	6.00~ 8.00	11~21	12~21	2.0~30.0(15.0)		15	8	M5	8	1.8	
	M	M	8T	6.00~ 8.00	11~21	12~21	2.0~30.0(15.0)		30	8	M4	6	1.8		
DAGKSTA	DAGKSTD	H S	Ġ	10	7.00~10.00	11~23	12~23	3.0~30.0(25.0)	0.5~10.0		10	M5	8	2.2	
DACKSTA	DASKSTD		H H	_	12	7.00~12.00	12~24	12~24	3.0~30.0(25.0)	İ	45	12	M5	8	2.5
				13	8.00~13.00	13~26	14~26	5.0~30.0 (25.0)		60	13	M8	10	3	
DASKSTA				16	10.00~16.00	16~32	16~32	5.0~30.0			16	M8	12	4	
				20	13.00~20.00	20~40	20~40	5.0~30.0			20	M8	12	5	

①B()尺寸适用于多棱型。